

## AUFW00049 Feast Watson Proofint Reducer Base

### Introduction

Part A  
**331 94765**

### Description and Image

**Feast Watson Proofint Reducer Base** is a stain medium to help extend the coverage, help avoid lap marks and slow the drying of Feast Watson Proofint.

### Features and Benefits

- Self levelling
- Increases the coverage of Proofint
- Touch dry after 1 hour
- Can be mixed at any ratio
- Helps to avoid lap marks
- Economical
- keeps a wet edge longer
- no colour fall out

### Uses

Formulated for use with Proofint.

### Precautions and Limitations

Application below 10°C or above 35°C is not advised.  
The drying time will vary greatly when the temperature is below 10°C or above 35°C or if the relative humidity is higher than 50%.

Always test colour on an off-cut or inconspicuous area prior to staining the whole job to ensure satisfaction with colour choice.

Note: That the dwell time before wiping excess, and the finishing clear coat will impact the final colour.

Typical Properties											
Colour	<b>CLEAR</b>										
Components	1										
V.O.C. Level	< <b>985g/L</b>										
Meets GBCA V.O.C. Requirements?	<b>No</b>										
Clean Up Description	Methylated spirits. To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.										
Application Conditions	<table border="1"> <thead> <tr> <th></th> <th>Min</th> <th>Max</th> <th>Recommended</th> </tr> </thead> <tbody> <tr> <td>Theoretical Spread Rate (m<sup>2</sup>/L)</td> <td><input type="text" value="10"/></td> <td><input type="text" value="20"/></td> <td><input type="text"/></td> </tr> </tbody> </table>				Min	Max	Recommended	Theoretical Spread Rate (m <sup>2</sup> /L)	<input type="text" value="10"/>	<input type="text" value="20"/>	<input type="text"/>
	Min	Max	Recommended								
Theoretical Spread Rate (m <sup>2</sup> /L)	<input type="text" value="10"/>	<input type="text" value="20"/>	<input type="text"/>								
Typical Property Notes	<p><b>Coverage</b> 10-20m<sup>2</sup>/L depending on the porosity of the timber.</p> <p><b>Dry times</b> Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Re-coat: 1 hour Top coat: 12 hours</p>										

Application Guide
<p>Surface Preparation</p> <p>Prepare new and previously coated timber as per the directions for Proofint.</p>
<p>Application Procedure and Equipment</p> <p>Always test colour on an off-cut or inconspicuous area prior to staining the whole job to ensure satisfaction with colour choice. Note: That the dwell time before wiping excess, and the finishing clear coat will impact the final colour.</p> <p>Proofint and Proofint Reducer Base may be mixed together in any ratio. The higher the level (or ratio) of Proofint added, the more intense the colour will become. The mixed Proofint and Reducer Base can be applied by 5-6mm nap roller, brush or pad applicator.</p> <p>Apply the mix to 2 or 3 boards at a time. To ensure an even finish, remove excess stain. This can be done using clean, dry rags or a dry roller. This excess stain can be re-applied to the next section, thus increasing spreading rates. Drying times will be affected by too much stain being left on the surface.</p>

Health and Safety	
SDS Number <b>DLXGHSEN001008</b>	SDS Link <a href="#">View SDS Link</a>
<p>Using Safety Precautions Flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness. Keep out of reach of children. Read the label before opening or using. Keep away from all sources of ignition – No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and all other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist, vapours or spray. Use only outdoors or in a well ventilated area. Wear protective clothing, gloves, eye/face protection and a suitable respirator as required. Wash hands, face and all exposed skin thoroughly after handling. Keep container tightly closed. Store locked up. Store in a well ventilated place, away from foodstuffs and oxidising agents. Keep cool. Do not empty into drains.</p>	
<p><b>Please refer to SDS Link. In case of emergency, please call 1800 220 770.</b></p>	

Transport and Storage	
Pack A <b>33194765</b>	
Size: <input type="text" value="4L"/>	Weight: <input type="text" value="4.32kg"/>
<p><b>Please refer to the Safety Data Sheet for full safety, health and transportation information.</b></p>	

Further Information
<a href="#">Product page</a>

**Disclaimer**

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from [www.duspecplus.com.au](http://www.duspecplus.com.au). Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.