

## AUFW00022 Feast Watson Proofint Colour Reducer

### Introduction

Part A  
**331 94933**

### Description and Image

**Feast Watson Proofint Colour Reducer** is a specially formulated dilution base for Feast Watson Proofint Traditional Stain. Using Proofint Colour Reducer enables the creation of lighter, more subtle timber shades. When staining large areas such as floors, Proofint Colour Reducer helps to distribute the stain, allowing more time for it to be spread, resulting in a consistent, even finish. Proofint Colour Reducer can be mixed with Proofint at any ratio to achieve the desired colour strength.



### Features and Benefits

- Formulated for use with Proofint.
- Can be mixed with Proofint in all ratios.

### Uses

Use to dilute or reduce Feast Watson Proofint.

### Precautions and Limitations

Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Do not apply in temperatures under 10°C or above 35°C.

### Performance Guide

Weather  
**Interior use only.**

### Typical Properties

Components  
**1**

Toxicity  
**Lead free.**

V.O.C. Level  
**< 985g/L**

Clean Up

#### Clean Up Description

Methylated spirits. To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.

## Application Methods

### Application Guide

#### Surface Preparation

Prepare new and previously coated timber as per the directions of Proofint. Seal soft, porous timbers such as Pine, Meranti and Cedar with Feast Watson Timber Primer prior to staining.

#### Application Procedure and Equipment

Proofint Colour Reducer should be stirred thoroughly before and during application with a flat blade stirrer taking care not to introduce bubbles. Mix Proofint with Proofint Colour Reducer to the desired rate. 1 part Proofint mixed with 1 part Proofint Colour Reducer will provide approximately half the colour strength of neat Proofint. Test colour on an off-cut or inconspicuous area prior to staining the whole job to ensure satisfaction with colour choice. Note that the dwell time before wiping excess, and the finishing clear coat will impact the final colour.

#### For Small Areas

For small and detailed areas, apply Proofint mix directly to the surface in the direction of the grain, by either brush or rag. Wipe off after 2-5 minutes depending on the depth of colour required. Allow to dry, then seal with Clear Varnish as per the label instructions.

#### For Large Areas

For large areas including floors, dilute Proofint in Proofint Colour Reducer which will give more working time to distribute the stain evenly. Apply with a rag, brush or Feast Watson Floor Finish Applicator in the direction of the grain. Wipe off excess after a period of time determined by the desired colour intensity. Allow to dry, then seal with Floorseal Oil, Floorclear or Floorproof Pro as per the label instructions as per the label instructions.

### Health and Safety

SDS Number  
**21068**

SDS Link  
[https://go.lupinsys.com/duluxgroup/harms/public/materials/35f7010af1be44e6a8669efe41e83792-published/attachments\\_api/7c894e1b750c99d9e33d9bc0ef718981/se-arch\\_api/331-94933\\_FEAST\\_WATSON\\_PROOFTINT\\_COLOUR\\_REDUCER-AUS\\_GHS.pdf](https://go.lupinsys.com/duluxgroup/harms/public/materials/35f7010af1be44e6a8669efe41e83792-published/attachments_api/7c894e1b750c99d9e33d9bc0ef718981/se-arch_api/331-94933_FEAST_WATSON_PROOFTINT_COLOUR_REDUCER-AUS_GHS.pdf)

#### Using Safety Precautions

Avoid contact with skin and eyes and breathing in vapour or spray mist. Wear overalls, impervious gloves and chemical goggles. Use only in well ventilated areas. If inhalation risk exists wear organic vapour/particulate respirator. Keep away from sources of heat or ignition - No smoking. Take precautionary measures against static discharges. Do not empty into drains. Keep containers closed when not in use.

**Please refer to SDS Link. In case of emergency, please call 1800 220 770.**

### Transport and Storage

Pack A  
**331 94933**

Size:

**250ml**

Weight:

**0.25Kg**

### Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as

recommended on the applicable Safety Data Sheets for the relevant products, available from [www.duspecplus.com.au](http://www.duspecplus.com.au). Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.