

AUFW00048 Feast Watson Scandinavian Oil

Introduction

Part A
870 94643

Description and Image

Feast Watson SCANDINAVIAN OIL is a clear blend of penetrating oils and polyurethane resin that gives an attractive protective finish on fine interior woodwork projects. SCANDINAVIAN OIL may be applied directly to raw or previously coated timber to provide a matt finish which can be built to a satin lustre by applying additional coats.



Features and Benefits

- Superior finish.
- Rejuvenates the timber.
- Fine, silky smooth matt to satin lustre finish.
- Highlights or restores the natural grain and colour of timber.
- Removes any accumulated scratches.
- Beautiful finish.

Uses

Ideal for all interior woodwork including furniture, architraves, trims, cedar blinds and panelling.

Precautions and Limitations


Do NOT apply in temperatures under 10°C or is likely to fall below 10°C during the drying period.
For interior use only.

Performance Guide

Weather
For interior use only.

Heat Resistance
Up to 100C.

Water
Good water resistance.

Typical Properties			
Gloss Level Matt			
Colour Clear			
Components 1		Number of Coats 2+	
Toxicity Lead free.		V.O.C. Level <525g/L	
Meets GBCA V.O.C. Requirements? No			
Touch Dry 4 hours			
Clean Up Description Mineral turpentine To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.			
Application Methods  Brush Clean soft cloth			
Application Conditions		Solids by Volume	
		<input type="text" value="34"/>	
Recoat Time (min/hours)		Min	Max
		<input type="text" value="8 hours"/>	<input type="text"/>
Theoretical Spread Rate (m ² /L)		Recommended	
		<input type="text" value="15"/>	<input type="text" value="18"/>
Typical Property Notes COVERAGE 15 to 18m ² per litre. DRYING TIME Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Touch Dry: 4 hours. Re-coat: 8 hours.			

Application Guide
<p>Surface Preparation</p> <p>New Timber Sand to a smooth surface and remove all sanding dust before coating. To achieve a super-smooth finish or if the timber grain is open or coarse, apply a coat of Feast Watson Sanding Sealer and sand back as per the directions.</p> <p>Previously Coated Timber Clean previously varnished surfaces with Feast Watson Floorclean and allow to dry.</p>
<p>Application Procedure and Equipment</p> <p>Surfaces to be coated must be dry and free from all dirt, dust, grease, wax and oil. Scandinavian Oil should be stirred thoroughly before and during application with a flat blade stirrer taking care not to introduce bubbles.</p> <p>New Timber Apply a coat of Scandinavian Oil using a clean soft cloth or pad, which is thoroughly saturated, or apply with a brush and then work the Scandinavian Oil into the timber with a clean soft cloth or pad. Allow to penetrate for 30 minutes. When the surface gets tacky remove excess surface oil with a clean dry cloth. Allow 8 hours between coats. Apply further coats until the desired finish is achieved.</p> <p>Coated Timber Apply using a scouring pad or fine steel wool (000). When the surface gets tacky remove excess surface oil with a clean dry cloth. Allow 8 hours between coats. Apply further coats until the desired finish is achieved. Three or four coats are recommended for a satin lustre and durable protection. More coats will increase the sheen.</p>

Health and Safety	
<p>SDS Number DLXGHSEN001208</p>	<p>SDS Link</p>
<p>Using Safety Precautions Flammable liquid and vapour. May be harmful if swallowed and enters airways. May cause an allergic skin reaction. May cause drowsiness or dizziness. Keep out of reach of children. Read the label before opening or using. Keep away from all sources of ignition - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and all other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Avoid breathing mist, vapours or spray. Wear protective clothing, gloves, eye/face protection and suitable respirator as required. Contaminated clothing should not be allowed out of the workplace. Wash contaminated clothing before use. Store locked up. Store in a well ventilated place and away from oxidizing agents and foodstuffs. Keep cool. Do not empty into drains.</p>	
<p>Please refer to SDS Link. In case of emergency, please call 1800 220 770.</p>	

Transport and Storage	
<p>Pack A 87094643</p>	
<p>Size: <input type="text" value="250ml 1L"/></p>	<p>Weight: <input type="text" value="0.29Kg 1.02Kg"/></p>
<p>Please refer to the Safety Data Sheet for full safety, health and transportation information.</p>	

Further Information

Product page

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.