

AUFW00048 Feast Watson Scandinavian Oil

Introduction

Part A
870 94643

Description and Image

Feast Watson SCANDINAVIAN OIL is a clear blend of penetrating oils and polyurethane resin that gives an attractive protective finish on fine interior woodwork projects. SCANDINAVIAN OIL may be applied directly to raw or previously coated timber to provide a matt finish which can be built to a satin lustre by applying additional coats.

Features and Benefits

- Superior finish.
- Rejuvenates the timber.
- Fine, silky smooth matt to satin lustre finish.
- Highlights or restores the natural grain and colour of timber.
- Removes any accumulated scratches.
- Beautiful finish.

Uses

Ideal for all interior woodwork including furniture, architraves, trims, cedar blinds and panelling.

Precautions and Limitations

Do NOT apply in temperatures under 10°C or is likely to fall below 10°C during the drying period..
For interior use only.

Performance Guide

| | |
|--|---|
| Weather For interior use only. | Heat Resistance Up to 120C. Premature yellowing and embrittlement will occur if subjected to continuous heat. |
| Water Good water resistance. | Abrasion Moderate resistance to abrasion. |

Typical Properties

| | |
|-------------------------------|------------------------------------|
| Gloss Level Matt | |
| Colour Clear | |
| Components 1 | Number of Coats 2+ |
| Toxicity Lead free. | V.O.C. Level < 560g/L |
| Touch Dry 4 hours | |
| Clean Up | |

Clean Up Description

Mineral turpentine

To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.

Application Methods



Brush



Pad

Application Conditions

Solids by Volume

32

Min

Max

Recommended

Wet Film Per Coat (microns)

56

Dry Film Per Coat (microns)

18

Recoat Time (min/hours)

8 hours

Theoretical Spread Rate (m²/L)

18

18

Typical Property Notes

COVERAGE

15 to 18m² per litre.

DRYING TIME

Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times.

Application Guide

Surface Preparation

New Timber

Sand to a smooth surface and remove all sanding dust before coating.

To achieve a super-smooth finish or if the timber grain is open or coarse, apply a coat of Feast Watson SANDING SEALER and sand back as per the directions.

Previously Coated Timber

Clean previously varnished surfaces with Feast Watson FLOORCLEAN and allow to dry.

Application Procedure and Equipment

Surfaces to be coated must be dry and free from all dirt, dust, grease, wax and oil.

SCANDINAVIAN OIL should be stirred thoroughly before and during application with a flat blade stirrer taking care not to introduce bubbles.

New Timber

Apply a coat of SCANDINAVIAN OIL using a clean soft cloth or pad, which is thoroughly saturated, or apply with a brush and then work the SCANDINAVIAN OIL into the timber with a clean soft cloth or pad.

Coated Timber

Apply using a scouring pad or fine steel wool (000).

Allow to penetrate for 30 minutes. When the surface gets tacky remove excess surface oil with a clean dry cloth.

Allow 8 hours between coats.

Apply further coats until the desired finish is achieved. Three or four coats are recommended for a satin lustre and durable protection. More coats will increase the sheen.

Health and Safety

SDS Number

2609

Using Safety Precautions

Irritating to skin. Avoid contact with skin and eyes. Use only in well ventilated areas. Keep windows and doors open during use and while drying. If inhalation risk exists wear organic vapour/particulate respirator.
Keep away from sources of ignition. Do NOT smoke. Keep containers closed when not in use.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A

870 94643

Size:

Weight:

4L 1 L 500ml 250ml

3.5Kg 0.9Kg 0.5Kg 0.3Kg

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.