

AUFW00045 Feast Watson Timber Primer

Introduction

Part A
870 94634

Description and Image

Feast Watson Timber Primer is a clear, water repellent penetrating wood preserver ideal for priming new interior and exterior timber. It has mould resistant properties and is designed to stabilise timber to minimise twisting and warping. Timber may be varnished or painted 12 hours after applying TIMBER PRIMER. TIMBER PRIMER is ideal for use on all timbers such as pergolas, window frames, undersides of flooring or lining boards, flooring joists and verandahs.

Also known as Fungshield.

Note: Timber Primer should not be used under penetrating coatings such as Feast Watson Wood Shield Oil, Decking Oil or Decking Stain.



Features and Benefits

- Penetrating wood preserver.
- For interior and exterior bare timber.
- Resists mould and decay.
- Minimise twisting and warping.

Uses

All timbers such as pergolas, window frames, undersides of flooring or lining boards, flooring joists and verandahs.

Precautions and Limitations

Timber Primer should not be used under penetrating coatings, for example Feast Watson Wood Shield Oil, Traditional Timber Oil, Water Repellent Timber & Decking Oil, Timber & Deck Stain, Outdoor Furniture Oil, Timber Floor Oil or Kitchen Timber Oil. It also should not be used under any water based coating.

Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times.




Do not apply in temperatures under 10°C or above 35°C or when rain or heavy dew is expected within the coating drying period.

Performance Guide

Weather
Interior and Exterior.

Heat Resistance
Up to 80C.

Water
Excellent.

Typical Properties			
Colour Clear			
Components 1		Number of Coats 1-2	
Toxicity Lead free		V.O.C. Level < 695g/L	
Meets GBCA V.O.C. Requirements? No			
Touch Dry 8 hours			
Clean Up Description Mineral turpentine To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.			
Application Methods <div>  Brush  Roller  Spray </div>			
Application Conditions		Solids by Volume	
		<input type="text" value="15"/>	
		Min	Max
Recoat Time (min/hours)	<input type="text" value="12 hours"/>	<input type="text"/>	<input type="text"/>
Theoretical Spread Rate (m ² /L)	<input type="text" value="8"/>	<input type="text" value="12"/>	<input type="text"/>
Typical Property Notes Coverage Softwoods: 8 - 10m ² per litre Hardwoods: 10 - 12m ² per litre Drying time Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Touch dry: 8 hours Top coat: 12 hours			

Application Guide

Surface Preparation

New Timber

Sand to a smooth surface and remove all sanding dust before coating.

Previously Coated Timber

Previously varnished surfaces need to be sanded to bare timber. Remove all sanding dust before coating.

Application Procedure and Equipment

Timber Primer should be stirred thoroughly before and during application with a flat blade stirrer. Apply a flood coat using a brush, roller or spray. Ensure edges and end grain are fully coated. A second coat may be necessary for porous timbers. Additional coats can be applied wet-on-wet. Allow surface to dry for 12 hours before overcoating with desired finish.

Health and Safety

SDS Number

DLXGHSEN001206

SDS Link

[View SDS Link](#)

Using Safety Precautions

Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause an allergic reaction. Causes serious eye irritation. May cause drowsiness and dizziness.

Keep out of reach of children. Read the label before opening or using. Keep away from all sources of ignition – No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and all other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist, vapours or spray. Use only outdoors or in a well ventilated area. Wear protective clothing, gloves, eye/face protection and a suitable respirator as required. Contaminated clothing should not be allowed out of the workplace. Wash contaminated clothing before re-use. Wash hands, face and all exposed skin thoroughly after handling. Keep container tightly closed. Store locked up. Store in a well ventilated place, away from oxidising agents and foodstuffs. Keep cool. Avoid release to the environment.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A

87094634

Size:

1L 4L

Weight:

1.00Kg 3.79Kg

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Further Information

[Product page](#)

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.