

AUFW00257 Feast Watson Timber Floor Oil

Introduction

Part A
872W0503

Description and Image

Feast Watson Timber Floor Oil is a ready to use Tung Oil blend that can be used straight from the can without the need for thinners or driers. The traditional, natural timber oil is carefully extracted from the nut of the Tung tree.

This beautiful oil penetrates deeply into timber and dries to a subtle matt finish. Simply wax and buff to achieve a lustrous sheen.

Feast Watson Timber Floor Oil is easy to apply and maintain, as you do not have to sand the surface prior.



Features and Benefits

- Tung Oil technology
- Perfectly blended for easy use
- Deeply penetrates
- 2 Hour touch dry
- Naturally clear

Uses

Suitable for use on cork, and all interior timber including floors, furniture, paneling and benchtops.




Precautions and Limitations

Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Do not apply in temperatures above 35°C or below 10°C.

Performance Guide

Weather
Interior only

Water
Good water resistance

Typical Properties			
Colour Clear			
Number of Coats 2			
V.O.C. Level <455g/L			
Meets GBCA V.O.C. Requirements? No			
Touch Dry 2 hours			
Clean Up Description Mineral turpentine To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.			
Application Methods <div>  Brush  Roller  Pad </div> Cloth			
Application Conditions		Solids by Volume	
		<input type="text" value="43"/>	
		Min	Max
Theoretical Spread Rate (m ² /L)	<input type="text" value="10"/>	<input type="text" value="12"/>	<input type="text" value="Recommended"/>
Typical Property Notes COVERAGE 10 - 12m ² per litre, pending timber porosity. DRYING TIME Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Do not apply in temperatures above 35°C or below 10°C. Touch Dry: 2 hours. Re-coat: 24 hours.			

Application Guide

Surface Preparation

NEW OR BARE TIMBER/CORK

Punch exposed nails below the surface. Note that holes and imperfections should be filled with timber putty after the first coat of TIMBER FLOOR OIL to match the putty colour with the coated timber colour.

Sand timber to an even, smooth surface. Vacuum and wipe to remove dust.

Prepare cork according to cork manufacturers' instructions.

PREVIOUSLY COATED TIMBER

Clean surface with Feast Watson FLOORCLEAN and allow to dry.

Previous polyurethane coatings or varnishes need to be removed by sanding surface back to bare timber.

Previous coatings of TIMBER FLOOR OIL can be recoated without resanding.

STAINING

If staining timber is desired complete these steps after the timber has been prepared and before applying TIMBER FLOOR OIL. If no staining is required the staining instructions can be disregarded.

Stain bare timber after sanding using PROOFTINT as per the application instructions.

Seal soft porous timbers such as pine with one coat of TIMBER FLOOR OIL before staining to ensure even absorption of the stain.

To stain flooring, mix PROOFTINT with Feast Watson PROOFTINT COLOUR REDUCER to allow time to evenly work the stain across the floor.

Test the mixture rate on off-cuts of flooring to confirm the colour before staining the whole area.

Apply stain to the floor with a FLOOR FINISH APPLICATOR as per PROOFTINT instructions.

Allow 12 hours to dry before applying TIMBER FLOOR OIL.

Application Procedure and Equipment

Surfaces to be coated must be dry and free from all dirt, dust, grease, wax, polish and oil.

TIMBER FLOOR OIL should be stirred thoroughly before and during application with a flat blade stirrer taking care not to introduce bubbles.

Apply a liberal coat of TIMBER FLOOR OIL to the timber with a brush, roller, cloth or Feast Watson® FLOOR FINISH APPLICATOR. Ensure the surface is evenly covered.

Leave the TIMBER FLOOR OIL to soak into timber for approximately 60 minutes and then wipe off any excess product with a clean cloth.

When the first coat is thoroughly dry, apply a second coat of TIMBER FLOOR OIL following the application process outlined above.

When applying TIMBER FLOOR OIL to floors, buff the floor after the final coat using a buffing machine (300 revs/minute). Allow 24 hours before buffing.

MAINTENANCE

Regularly clean floors using FLOORCLEAN.

When surface requires an additional coat, clean with FLOORCLEAN and apply one coat of TIMBER FLOOR OIL as per application directions.

Health and Safety

SDS Number

DLXGHSEN004188

SDS Link

Using Safety Precautions

Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness.

Keep out of reach of children. Read carefully and follow all instructions. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing dust, fume, gas, mist, vapours or spray. Wash hands, face and all exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing including eye/face protection and suitable respirator.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A

872W0503

Size:

Weight:

1L 4L

1.00Kg 3.81Kg

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.