

Feast Watson Mastertouch Wipe On Poly Gloss

AU_DW01996

Part A	917W0094
---------------	----------

Description

Feast Watson MASTERTOUCHE WIPE-ON POLY is a clear, silky smooth, oil based polyurethane finish that provides durable protection with classic, hand-rubbed beauty. MASTERTOUCHE WIPE-ON POLY is easily applied with a cloth, without any drips or brush marks. MASTERTOUCHE WIPE-ON POLY is suitable for all interior woodwork including furniture, doors and windows, architraves, panelling and trim. MASTERTOUCHE WIPE-ON POLY is not suitable for high traffic areas such as floors. For flooring use Feast Watson FLOORCLEAR.

Features

- Wipe on finish
- Oil based polyurethane.
- Easy to apply.

Benefits

- Classic, hand-rubbed beauty.
- Durable protection.
- No drips or brush marks.

Uses

All interior woodwork including furniture, doors and windows, architraves, panelling and trim.

Precautions And Limitations

MASTERTOUCHE WIPE-ON POLY is not suitable for high traffic areas such as floors.
Soak application cloths in water before disposal.

Performance Guide

Weather	Interior only.	Salt	Good.
Heat Resistance	Up to 120C	Water	Good.
Solvent	Good for dilute solutions.	Abrasion	Not suitable for high traffic areas such as floors.
Acid	Good for dilute solutions.	Alkali	Good for dilute solutions.

Typical Properties																											
Gloss Level	Gloss	Colour	Clear.																								
Components	1	Number Of Coats	2+																								
V.O.C. Level	< 585g/L	Meets GBCA VOC Requirement?	No																								
Touch Dry	2 hours																										
Clean Up Description	Mineral turpentine To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.																										
Application Method	Other: Lint-free cloth.																										
Application Conditions	<table> <tr> <td>Solids By Volume</td><td>24</td><td></td><td></td></tr> <tr> <td></td><td>Min</td><td>Max</td><td>Recommended</td></tr> <tr> <td>Wet Film Per Coat (microns)</td><td></td><td></td><td></td></tr> <tr> <td>Dry Film Per Coat (microns)</td><td></td><td></td><td></td></tr> <tr> <td>Recoat Time (min)</td><td>6 hours</td><td></td><td></td></tr> <tr> <td>Theoretical Spread Rate (m²/L)</td><td></td><td>16</td><td></td></tr> </table>			Solids By Volume	24				Min	Max	Recommended	Wet Film Per Coat (microns)				Dry Film Per Coat (microns)				Recoat Time (min)	6 hours			Theoretical Spread Rate (m²/L)		16	
Solids By Volume	24																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)																											
Dry Film Per Coat (microns)																											
Recoat Time (min)	6 hours																										
Theoretical Spread Rate (m²/L)		16																									
Typical Properties Notes	<p>DRYING TIME Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Touch Dry: 2 hours Recoat: 6 hours</p> <p>COVERAGE Up to 16m² per litre.</p>																										

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> Fill nail holes, cracks and other defects with a Water Based Putty after applying the first coat of this product for accurate colour matching. Remove stains, dirt, wax, grease and oil with mineral turpentine. Remove any polish with a suitable polish remover. <p>BARE TIMBER Sand to a smooth surface and remove all sanding dust before coating. For naturally oily timbers, seal the timber with Feast Watson PROOFSEAL™ as per the directions prior to application.</p> <p>PREVIOUSLY COATED TIMBER Previously varnished surfaces need to be sanded to a dull finish. Remove all sanding dust before coating. Thoroughly clean the surface with FLOOR CLEAN and allow to dry. Apply one coat to a small test area. Allow to dry for 6 hours. Press sticky tape firmly to the surface and pull off quickly. If the coating comes off, sand back to bare timber. If coating adheres well, sand the entire area with 180 - 240 grit paper for good adhesion, remove dust, then follow application instructions.</p>
Application Procedure And Equipment	<ul style="list-style-type: none"> Shake MASTERTOUCHE WIPE-ON POLY container for one minute prior to use. <p>INTERIOR TIMBER Apply a liberal amount with a clean lint free cloth in the direction of the grain. Allow to dry for a minimum of 6 hours. Subsequent coats can be applied as required following instructions above. A light sand with 240 grit sand paper is recommended between coats.</p> <p>STAINING Apply Feast Watson PROOFTINT™ following label directions prior to the application of MASTERTOUCHE WIPE-ON POLY. Allow PROOFTINT to dry the recommended period before applying MASTERTOUCHE WIPE-ON POLY.</p> <p>MAINTENANCE Regularly monitor the surface for signs of colour loss or surface defects. When required, lightly sand the surface and remove dust. Recoat with additional coats of MASTERTOUCHE WIPE-ON POLY as per application instructions.</p>

Health And Safety			
MSDS Number	23261	Using Safety Precautions	Keep out of reach of children. Avoid contact with skin and eyes. Provide adequate ventilation. If using indoors keep windows and doors open during use and while drying. If painting large areas wear an organic vapour respirator. This paint is flammable, so eliminate any sources of ignition. Do not smoke.
Health Effects	<p>FIRST AID: For advice contact a Doctor or Poisons Information Centre on AUST 13 11 26, NZ 0800 764 766.</p> <p>SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical assistance.</p> <p>EYE: Rinse with plenty of running water. Seek medical help if irritation occurs.</p> <p>SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water.</p> <p>For further information or a copy of the Product Safety Data Sheet telephone Feast Watson Customer Service Department on AUST 1800 252 502, NZ 0800 222 687.</p> <p>FOR EMERGENCIES call AUST 1800 033 111, NZ 0800 734 607.</p>	Flammability	This product is flammable.
Storage	Keep out of reach of children.	Disposal	Soak application cloths in water before disposal. Do NOT pour leftover product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collections. Empty containers should be left open in a well ventilated area to dry out. When dry, recycle the container via steel can recycling programs. Disposal of empty containers via domestic recycling programs may differ between local authorities. Check with your local council/Waste Management Authority first.
In the case of emergency, please call 1800 033 111			

Transport And Storage			
Pack A	917W0094	Shipment Name	PAINT
Size 1L	Weight 1kg		
Flash Point	>23C	UN Number	1263
Dangerous Goods Class	3	Package Group	III

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427