

AUFW00023 Feast Watson Mastertouch Polish

Introduction

Part A
917 94669

Description and Image

Feast Watson MASTERTOUC POLISH is unique combination of refined oils to restore and enhance the natural beauty of timber. MASTERTOUC POLISH will rejuvenate coatings and help to diminish fine scratches. MASTERTOUC POLISH is silicone free to help protect the timber coating.

Features and Benefits

- Use on all timber surfaces
- Silicon free
- Can be used as a floor polish
- Easily re-coated

Uses



Use FEAST WATSON Mastertouch Polish to restore the natural beauty of timber finishes back to a bright lustre. Mastertouch removes all fine scratches that develop on floors and furniture from general wear and tear.

Precautions and Limitations

Not suitable for uncoated timber.
Floors will be slippery whilst wet.
Soak application cloths in water before disposal.

Performance Guide

Weather For interior use only	Heat Resistance Up to 120C. Premature yellowing and embrittlement will occur if subjected to continuous heat.
Water Good water resistance.	Abrasion Moderate resistance to abrasion.

Typical Properties	
Colour Clear	
Components 1	Number of Coats 1
Toxicity Lead free. Dry film is non-toxic and conforms to AS1647, Part 3.	V.O.C. Level < 130g/L
Touch Dry 2 hours	
Clean Up  Water	
Clean Up Description Warm soapy water	
Application Methods  Pad Mop or cloth	

Application Guide
Surface Preparation Bare Timber Not suitable for uncoated timber. Coated Timber Surfaces must be clean & dry.
Application Procedure and Equipment Floors Pour MASTERTOUCHE Polish directly onto a water dampened applicator or mop. Wipe sparingly over the floor. Polish off using a soft dry cloth. Warning: Floors will be slippery whilst wet. Furniture Pour MASTERTOUCHE Polish directly onto a soft, damp cloth. Wipe sparingly over the timber furniture. Polish off using a soft dry cloth.

Health and Safety	
SDS Number 4160	SDS Link
Using Safety Precautions Avoid contact with skin and eyes. Provide adequate ventilation. Wash hands after use.	
Please refer to SDS Link. In case of emergency, please call 1800 220 770.	

Transport and Storage

Pack A

917-94669

Size:

Weight:

375ml 250ml

400g 300g

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.