

Feast Watson Sanding Sealer

AUDW0744

Part A	870 94641
---------------	-----------

Description

Feast Watson SANDING SEALER levels rough surfaces to create flawless, mirror finish coatings. SANDING SEALER is a clear and quickly dries to a hard film which fills open grain and marked timbers. SANDING SEALER can be dry sanded to create a super smooth finish with no grain pattern. Top-coat SANDING SEALER with Feast Watson CLEAR VARNISH, WEATHERPROOF VARNISH or STAIN & VARNISH. It is also a perfect preparation to remove grain texture from timber prior to French polishing or painting.

Features

- Clear wood sealer
- Fills grain & sands easily
- Quick drying

Benefits

- For preparing porous open grained timber for clear polyurethanes.
- Gives a better, smoother finish with less effort.
- Reduces time on the job.

Uses

Use FEAST WATSON Sanding Sealer as an interior timber grain sealer prior to applying FEAST WATSON oil or water based polyurethanes, to give a smooth finish to the topcoats.

Precautions And Limitations

Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Do not apply in temperatures under 10°C or above 35°C.

Performance Guide

Weather	Interior use only.	Solvent	.
----------------	--------------------	----------------	---

Typical Properties																											
Colour	Dries to colourless clear, although it appears milky in the can.	Components	1																								
Number Of Coats	1	Toxicity	Lead free.																								
V.O.C. Level	< 525g/L	Touch Dry	3 hours																								
Clean Up Description	Mineral turpentine To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.																										
Application Method	 Air Spray  Brush  Roller																										
Application Conditions	<table> <tr> <td>Solids By Volume</td><td>35</td><td></td><td></td></tr> <tr> <td></td><td>Min</td><td>Max</td><td>Recommended</td></tr> <tr> <td>Wet Film Per Coat (microns)</td><td></td><td></td><td>100</td></tr> <tr> <td>Dry Film Per Coat (microns)</td><td></td><td></td><td>35</td></tr> <tr> <td>Recoat Time (min)</td><td>6 hours</td><td>Indefinite</td><td></td></tr> <tr> <td>Theoretical Spread Rate (m²/L)</td><td></td><td>10</td><td>10</td></tr> </table>			Solids By Volume	35				Min	Max	Recommended	Wet Film Per Coat (microns)			100	Dry Film Per Coat (microns)			35	Recoat Time (min)	6 hours	Indefinite		Theoretical Spread Rate (m²/L)		10	10
Solids By Volume	35																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)			100																								
Dry Film Per Coat (microns)			35																								
Recoat Time (min)	6 hours	Indefinite																									
Theoretical Spread Rate (m²/L)		10	10																								
Typical Properties Notes	<p>COVERAGE 8 - 10 m² per litre.</p> <p>DRYING TIME Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times.</p>																										

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> New Timber Sand timber and remove all sanding dust before coating. Previously Coated Timber Previously coated surfaces need to be sanded to bare timber. Remove all sanding dust before coating.
Application Procedure And Equipment	<ul style="list-style-type: none"> Apply SANDING SEALER using a brush, roller or spray gun. If applying by spray, add 20% of mineral turpentine to thin product. Allow to dry before sanding off all surface material with medium grade sand paper. Apply 1-2 coats of SANDING SEALER depending on grain depth. Two or more coats may be required when applying by spray. Thoroughly remove all dust from the surface prior to applying finish coats. STAINING Apply Feast Watson PROOFTINT stain after the final SANDING SEALER coat has been sanded, and prior to the application of top coats. Top Coats Finish by coating the surface with CLEAR VARNISH, WEATHERPROOF VARNISH or STAIN & VARNISH following the label instructions.

Health And Safety

MSDS Number	1280	Using Safety Precautions	Avoid contact with skin and eyes. Provide adequate ventilation. If using indoors keep windows and doors open during use and while drying. If painting large areas wear an organic vapour respirator. This paint is flammable, so eliminate any sources of ignition. Do not smoke.
Health Effects	<p>FIRST AID: For advice, contact a Poisons Information Centre (Phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor.</p> <p>SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical assistance.</p> <p>EYE: Rinse with plenty of running water. Seek medical help if irritation occurs.</p> <p>SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water.</p>	Flammability	This product is flammable
Protective Equipment	Wear eye protection, protective clothing and gloves.	Storage	Keep out of reach of children.
Disposal	Do not pour leftover paint down the drain. Unwanted paint should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collections. Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.		
In the case of emergency, please call 1800 033 111			

Transport And Storage

Pack A	870-94641	Shipment Name	PAINT
Size	4 Litre 1 Litre 500ml 250ml	Weight	4.2 Kg 1.1 Kg 524g 262g
Flash Point	>23C	UN Number	1263
Dangerous Goods Class	3	Package Group	III

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427