

AUFW00021 Feast Watson Sanding Sealer

Introduction

Part A
870 94641

Description and Image

Feast Watson Sanding Sealer levels rough surfaces to create flawless, mirror finish coatings. Sanding Sealer is a clear and quickly dries to a hard film which fills open grain and marked timbers. Sanding Sealer can be dry sanded to create a super smooth finish with no grain pattern. Top-coat Sanding Sealer with Feast Watson Clear Varnish, Weatherproof Varnish or Stain & Varnish. It is also a perfect preparation to remove grain texture from timber prior to French polishing or painting.



Features and Benefits

- Clear wood sealer
- Fills grain & sands easily
- Quick drying
- For preparing porous open grained timber for clear polyurethanes.
- Gives a better, smoother finish with less effort.
- Reduces time on the job.

Uses

Use Feast Watson Sanding Sealer as an interior timber grain sealer prior to applying Feast Watson oil or water based polyurethanes, to give a smooth finish to the topcoats.

Precautions and Limitations

Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Do not apply in temperatures under 10°C or above 35°C.

Performance Guide

Weather
Interior use only.

Typical Properties

Heat Thinner
Mineral turpentine

Colour
Dries to colourless clear, although it appears milky in the can.

Components
1

Number of Coats
1-2

Toxicity
Lead free.

V.O.C. Level
< 515g/L

Meets GBCA V.O.C. Requirements?
No

Touch Dry
2-4 hours

Clean Up Description
Mineral turpentine
To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.

Application Methods



Brush



Roller



Spray

Application Conditions

Solids by Volume

36

Min

Max

Recommended

Wet Film Per Coat (microns)

100

Dry Film Per Coat (microns)

35

Recoat Time (min/hours)

6 hours

Theoretical Spread Rate (m²/L)

8

10

10.29

Typical Property Notes

Coverage

8 - 10 m² per litre.

Drying Time

Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times.

Sanding time: Allow 6 hours before sanding

Touch dry: 2 - 4 hours

Application Guide

Surface Preparation

New Timber

Sand timber and remove all sanding dust before coating.

Previously Coated Timber

Previously coated surfaces need to be sanded to bare timber. Remove all sanding dust before coating.

Application Procedure and Equipment

Apply Sanding Sealer using a brush, roller or spray gun.

If applying by spray, add 20% of mineral turpentine to thin product.

Allow to dry before sanding off all surface material with medium grade sand paper.

Apply 1-2 coats of Sanding Sealer depending on grain depth. Two or more coats may be required when applying by spray.

Thoroughly remove all dust from the surface prior to applying finish coats.

Staining

Apply Feast Watson Proofint stain after the final Sanding Sealer coat has been sanded, and prior to the application of top coats.

Top Coats

Finish by coating the surface with Clear Varnish, Weatherproof Varnish or Stain & Varnish following the label instructions.

Health and Safety

SDS Number

DLXGHSEN001207

SDS Link

[View SDS Link](#)

Using Safety Precautions

Flammable liquid and vapour. May cause an allergic skin reaction. May cause drowsiness or dizziness.

Keep out of reach of children. Read the label before opening or using. Keep away from all sources of ignition - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion - proof electrical, ventilating, lighting and all other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Avoid breathing mist, vapours or spray. Wear protective clothing, gloves, eye/face protection and suitable respirator as required. Contaminated clothing should not be allowed out of the workplace. Wash contaminated clothing before use. Store locked up. Store in a well ventilated place and away from oxidizing agents and foodstuffs. Keep cool. Do not empty into drains.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A

87094641

Size:

250ml 1L

Weight:

0.33Kg 1.18Kg

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Further Information

[Product page](#)

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.