

AUFW00068 Feast Watson Fine Buffing Oil

Introduction

Part A
870 94632

Description and Image

Feast Watson Fine Buffing Oil is a special blend of beeswax, carnauba wax and tung oil ideal for a traditional hand rubbed finish on all fine woodwork. When applied and buffed, it imparts a mellow soft lustre that gives a tougher, more resilient film than a wax polish. Fine Buffing Oil is ideal for rejuvenating tired and worn coated interior timber surfaces without having to sand the original coating.

Features and Benefits

- Blend of waxes and natural oils
- Soft lustre
- Clear finish
- Gives a traditional "hand-rubbed" appearance
- Rejuvenates coated interior timber
- Enhances grain and colour

Uses


Interior furniture, architraves, doors and other woodwork.

Precautions and Limitations

Fine Buffing Oil can be applied directly to raw timber, however for best results timber should be sealed.
Do not apply in temperatures under 10°C or above 35°C.

Performance Guide

Weather Interior use only.	Heat Resistance Up to 100C. Premature yellowing and embrittlement will occur if subjected to continuous heat.
Water Good water resistance.	Abrasion Moderate resistance to abrasion.

Typical Properties			
Colour Clear			
Components 1		Number of Coats 1 minimum	
V.O.C. Level < 595g/L			
Meets GBCA V.O.C. Requirements? No			
Touch Dry 6 hours			
Clean Up Description Mineral turpentine To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.			
Application Methods  Brush Soft cloth, Nylon scouring pad, Steel wool (000)			
Application Conditions	Solids by Volume		
	<input type="text" value="26"/>		
	Min	Max	Recommended
Wet Film Per Coat (microns)	<input type="text"/>	<input type="text"/>	<input type="text" value="50"/>
Dry Film Per Coat (microns)	<input type="text"/>	<input type="text"/>	<input type="text" value="13"/>
Recoat Time (min/hours)	<input type="text" value="12 hours"/>	<input type="text"/>	<input type="text"/>
Theoretical Spread Rate (m ² /L)	<input type="text"/>	<input type="text"/>	<input type="text" value="20"/>
Typical Property Notes Coverage 20m ² per litre Drying time Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Touch Dry: 6 hours Re-coat / Dry: 12 hours			

Application Guide
<p>Surface Preparation</p> <p>New Timber Sand to a smooth surface and remove all sanding dust before coating. Fine Buffing Oil can be applied directly to raw timber, however for best results timber should be sealed. Seal bare timber with Feast Watson Proofseal as per the directions. To achieve a super-smooth finish or if the timber grain is open or coarse, seal with Feast Watson Sanding Sealer and sand back as per the directions.</p> <p>Previously Coated Timber Clean previously varnished surfaces with Feast Watson Floorclean and allow to dry.</p>
<p>Application Procedure and Equipment</p> <p>Surfaces to be coated must be dry and free from all dirt, dust, grease, wax and oil. Stir Fine Buffing Oil thoroughly before and during use with a broad flat stirrer. Apply Fine Buffing Oil with a nylon scouring pad or with fine steel wool (000). Apply in the direction of the grain. For soft timbers such as pine, apply using a soft cloth. Allow Fine Buffing Oil to penetrate 10-20 minutes. When the surface gets tacky wipe vigorously with a coarse cloth. Leave for approximately 5 hours then buff surface with a soft clean cloth.</p> <p>Maintenance Regularly monitor the surface for signs of colour loss or surface defects. When required, wash surface with Feast Watson Floorclean and repeat the application process above.</p>

Health and Safety	
<p>SDS Number DLXGHSEN001388</p>	<p>SDS Link View SDS Link</p>
<p>Using Safety Precautions Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful in contact with skin and if inhaled. Causes skin irritation. May cause an allergic skin reaction. Read the label before opening or using. Keep away from all sources of ignition – No smoking. Avoid breathing mist, vapours or spray. Wear protective clothing, gloves, eye/face protection and a suitable respirator as required. Store in a well ventilated place, away from foodstuffs and oxidizing agents. Keep cool. Do not empty into drains.</p>	
<p>Please refer to SDS Link. In case of emergency, please call 1800 220 770.</p>	

Transport and Storage	
<p>Pack A 87094632</p>	
<p>Size: <input type="text" value="250ml 1L"/></p>	<p>Weight: <input type="text" value="0.28Kg 1.01Kg"/></p>
<p>Please refer to the Safety Data Sheet for full safety, health and transportation information.</p>	

Further Information
<p>Product page</p>

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.