

Feast Watson Outdoor Furniture Oil

AUDW0728

| | |
|---------------|----------|
| Part A | 840-Line |
|---------------|----------|

Description

Feast Watson OUTDOOR FURNITURE OIL has been specially formulated to preserve and maintain the natural look of outdoor timber settings. OUTDOOR FURNITURE OIL has UV and mould resistant properties with excellent water resistance and is available in a range of timber tones. With added eucalyptus oil, Feast Watson OUTDOOR FURNITURE OIL penetrates deeply into the timber and will not crack or peel.

NOTE: OUTDOOR FURNITURE OIL 'Clear' is not recommended to withstand extreme conditions and direct sunlight. The timber toned OUTDOOR FURNITURE OILS enhance and extend the life of the natural timber colour by allowing higher levels of UV protection to be added for longer lasting protection.

Features

- Penetrating film
- Transparent
- Matt finish

Benefits

- Will not crack or flake
- Allows grain and texture to show
- Gives natural look to timber

Uses


All exterior timber furniture.

Precautions And Limitations

Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Do not apply in temperatures under 10°C or above 35°C or when rain or heavy dew is expected within the coating dry time. Soak application cloths in water before disposal.

Performance Guide

| | | | |
|------------------------|-----------|-----------------|------|
| Weather | Good | Salt | Good |
| Heat Resistance | Up to 80C | Water | Good |
| Solvent | Fail | Abrasion | Fair |
| Acid | Fair | Alkali | Fair |

| Typical Properties | | | |
|---------------------------------|---|-------------------|--------------------|
| Colour | 4 timber tones plus Clear | Components | 1 |
| Number Of Coats | 2 | Toxicity | Lead free |
| V.O.C. Level | < 610g/L | Touch Dry | 6 hours |
| Clean Up Description | Mineral turpentine. To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other. | | |
| Application Method |  Brush | | |
| Application Conditions | | Min | Max |
| | Wet Film Per Coat (microns) | | Recommended |
| | Dry Film Per Coat (microns) | | |
| | Recoat Time (min) | 12 hours | |
| | Theoretical Spread Rate (m²/L) | | |
| Typical Properties Notes | <p>COVERAGE 500ml should provide 2 coats for an average 3 piece outdoor setting, while 1 litre should provide 2 coats for an average 5 piece outdoor setting.</p> <p>DRYING TIME Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times.</p> | | |

| Application Guide | |
|--|--|
| Surface Preparation | <ul style="list-style-type: none"> New Timber Allow new timber to weather in its final position for 4-6 weeks. Prepare timber for coating with Feast Watson WOODCLEAN as per the instructions. For best results, lightly sand the surface to remove any grain raise. Remove all sanding dust before coating. Weathered Timber Prepare weathered or grey timber by cleaning thoroughly with WOODCLEAN as per the instructions. Sanding may be required to remove stains and restore deteriorated surfaces. Remove all sanding dust before coating. Previously Coated Timber Timber coated with stain or oil can be coated with OUTDOOR FURNITURE OIL after the surface has weathered. Test if the surface is ready by sprinkling water onto the timber, if the water absorbs into the timber it is suitable for coating. If the water beads, further weathering, sanding or stripping is required. Painted or varnished surfaces need to be taken back to bare timber by stripping or sanding. Prepare timber for coating with WOODCLEAN as per the instructions. |
| Application Procedure And Equipment | <ul style="list-style-type: none"> Allow the timber to dry completely before applying OUTDOOR FURNITURE OIL OUTDOOR FURNITURE OIL should be stirred thoroughly before and during application with a flat blade stirrer taking care not to introduce bubbles. If the job requires more than one can of OUTDOOR FURNITURE OIL, mix all together in one large container prior to commencing. Apply one coat of OUTDOOR FURNITURE OIL using a brush or spray. If applying with a spray, back brush the coating to ensure even penetration. Work along 3-4 planks at a time, in the direction of the grain. Ensure edges and end grain are fully coated. Allow first coat to dry for 12 hours before applying a second coat. MAINTENANCE Regularly monitor coated timber for signs of colour loss, dryness and weathering. If required, clean the surface using WOODCLEAN, allow the surface to dry and recoat with one coat of OUTDOOR FURNITURE OIL. |

| Health And Safety | | | |
|---|---|---------------------------------|--|
| MSDS Number | 1231 | Using Safety Precautions | Avoid contact with skin and eyes. Provide adequate ventilation. This product is flammable, so eliminate any sources of ignition. Do NOT smoke. |
| Health Effects | Irritating to skin. May cause sensitisation by skin contact. Harmful: May cause lung damage if swallowed. FIRST AID For advice contact a Poisons Information Centre, Phone 13 11 26; New Zealand 0800 764 766, or a doctor. Swallowed: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical assistance. Eye: If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor. Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. | Flammability | This product is flammable |
| Protective Equipment | Wear eye protection, protective clothing and gloves. | Storage | Keep out of reach of children. |
| Disposal | Do NOT pour leftover product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collections. Empty containers should be left open in a well ventilated area to dry out. When dry, recycle the container via steel can recycling programs. Disposal of empty containers via domestic recycling programs may differ between local authorities. Check with your local council/Waste Management Authority first. | | |
| In the case of emergency, please call 1800 033 111 | | | |

| Transport And Storage | | | |
|------------------------------|----------|----------------------|--------------|
| Pack A | 840-Line | Shipment Name | PAINTS |
| Size | 1L 500ml | Weight | 1.0kg 0.54kg |
| Flash Point | >23c | UN Number | 1263 |
| Dangerous Goods Class | 3 | Package Group | III |

Disclaimer

Dulux, Selleys and Other marks followed by © are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by © are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427