

AUFW00076 Feast Watson Outdoor Furniture Oil

Introduction

Part A
840-Line

Description and Image

Feast Watson Outdoor Furniture Oil has been specially formulated to preserve and maintain the natural look of outdoor timber settings. Outdoor Furniture Oil has UV and mould resistant properties with excellent water resistance and is available in a range of timber tones. With added eucalyptus oil, Feast Watson Outdoor Furniture Oil penetrates deeply into the timber and will not crack or peel.

Note: Outdoor Furniture Oil 'Clear' is not recommended to withstand extreme conditions and direct sunlight. The timber toned Outdoor Furniture Oil enhance and extend the life of the natural timber colour by allowing higher levels of UV protection to be added for longer lasting protection.



Features and Benefits

- Penetrating film
- Transparent
- Matt finish
- Will not crack or flake
- Allows grain and texture to show
- Gives natural look to timber

Uses

All exterior timber furniture.

Precautions and Limitations



Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Do not apply in temperatures under 10°C or above 35°C or when rain or heavy dew is expected within the coating dry time.

Performance Guide

Weather
Good

Heat Resistance
Up to 100C

Water
Good

Typical Properties			
Colour 4 timber tones plus Clear			
Components 1		Number of Coats 2	
Toxicity Lead free		V.O.C. Level < 620g/L	
Meets GBCA V.O.C. Requirements? No			
Touch Dry 6 hours			
Clean Up Description Mineral turpentine. To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.			
Application Methods  Brush  Spray			
Application Conditions	Solids by Volume <input type="text" value="20"/>		
Recoat Time (min/hours)	Min <input type="text" value="12 hours"/>	Max <input type="text"/>	Recommended <input type="text"/>
Theoretical Spread Rate (m ² /L)	<input type="text" value="6"/>	<input type="text" value="10"/>	<input type="text"/>
Typical Property Notes Coverage 6 - 10m ² per litre. 500ml should provide 2 coats for an average 3 piece outdoor setting, while 1 litre should provide 2 coats for an average 5 piece outdoor setting. Drying time Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Touch Dry: 6 hours Recoat: 12 hours			

Application Guide

Surface Preparation

New Timber
Allow new timber to weather in its final position for 4-6 weeks.
Prepare timber for coating with Feast Watson Woodclean as per the instructions.
For best results, lightly sand the surface to remove any grain raise. Remove all sanding dust before coating.

Weathered Timber
Prepare weathered or grey timber by cleaning thoroughly with Woodclean as per the instructions.
Sanding may be required to remove stains and restore deteriorated surfaces. Remove all sanding dust before coating.

Previously Coated Timber
Timber coated with stain or oil can be coated with Outdoor Furniture Oil after the surface has weathered. Test if the surface is ready by sprinkling water onto the timber, if the water absorbs into the timber it is suitable for coating. If the water beads, further weathering, sanding or stripping is required.
Painted or varnished surfaces need to be taken back to bare timber by stripping or sanding.
Prepare timber for coating with Woodclean as per the instructions.

Application Procedure and Equipment

Allow the timber to dry completely before applying Outdoor Furniture Oil
Outdoor Furniture Oil should be stirred thoroughly before and during application with a flat blade stirrer taking care not to introduce bubbles.
If the job requires more than one can of Outdoor Furniture Oil, mix all together in one large container prior to commencing.
Apply one coat of Outdoor Furniture Oil using a brush or spray. If applying with a spray, back brush the coating to ensure even penetration. Work along 3-4 planks at a time, in the direction of the grain. Ensure edges and end grain are fully coated.
Allow first coat to dry for 12 hours before applying a second coat.

Do not apply in temperatures under 10°C or above 35°C or when rain or heavy dew is expected within the coating dry time.

Maintenance
Regularly monitor coated timber for signs of colour loss, dryness and weathering.
If required, clean the surface using Woodclean, allow the surface to dry and recoat with one coat of Outdoor Furniture Oil.

Health and Safety

SDS Number DLXGHSEN001211	SDS Link View SDS Link
-------------------------------------	---

Using Safety Precautions
Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. May cause drowsiness or dizziness.
Keep out of reach of children. Read the label before opening or using. Keep away from all sources of ignition - No smoking. Keep container tightly closed. Store locked up. Store in a well ventilated place and away from oxidising agents and foodstuffs. Keep cool. Avoid release to the environment.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A
840-Line

Size: 500ml 1L	Weight: 0.54Kg 1.00Kg
--------------------------	---------------------------------

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Further Information

Product page

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.