

## Feast Watson Paving & Sandstone Sealer

**AUDW0752**

Part A	872 94657
--------	-----------

### Description

Feast Watson PAVING & SANDSTONE SEALER is a UV resistant clear coating which under normal circumstances does not crack or peel. It is formulated to give lasting stain and wear protection to interior and exterior surfaces. PAVING & SANDSTONE SEALER is ideal for use on stamped concrete, sandstone and concrete masonry pavers, terracotta roof tiles and natural brick.

PAVING & SANDSTONE SEALER is not recommended for use over acrylic bound pebbles or glazed tiles. Caution: Smooth surfaces may become slippery when wet.

### Features

- Non yellowing
- Clear film
- Heavy duty

### Benefits

- Suitable for interior and exterior use
- Enhances natural colour and texture of masonry and sandstone
- Tough, hard wearing

### Uses




On stamped concrete, sandstone and concrete masonry pavers, terracotta roof tiles and natural brick.

### Precautions And Limitations

Do not apply in temperatures under 10°C or above 35°C or when rain or heavy dew is expected within the coating dry time.

### Performance Guide

<b>Weather</b>	For interior and exterior use	<b>Salt</b>	Unaffected by splash or spillage
<b>Heat Resistance</b>	Up to 120C.	<b>Water</b>	Excellent
<b>Solvent</b>	Resists alcohol and hydrocarbons.	<b>Abrasion</b>	Excellent
<b>Acid</b>	Suitable for splash (dilute only)	<b>Alkali</b>	Suitable for splash (dilute only)

Typical Properties																											
Colour	Clear	Components	1																								
Number Of Coats	2	Toxicity	Lead free. Dry film is non-toxic and conforms to AS1647, Part 3.																								
V.O.C. Level	< 710g/L	Touch Dry	1 hour																								
Clean Up Description	Xylene To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.																										
Application Method	 Brush  Roller  Pad																										
Application Conditions	<table> <tr> <td><b>Solids By Volume</b></td><td>17</td><td></td><td></td></tr> <tr> <td></td><td><b>Min</b></td><td><b>Max</b></td><td><b>Recommended</b></td></tr> <tr> <td><b>Wet Film Per Coat (microns)</b></td><td></td><td></td><td>100</td></tr> <tr> <td><b>Dry Film Per Coat (microns)</b></td><td></td><td></td><td>17</td></tr> <tr> <td><b>Recoat Time (min)</b></td><td>2 hours</td><td></td><td></td></tr> <tr> <td><b>Theoretical Spread Rate (m<sup>2</sup>/L)</b></td><td></td><td>12</td><td>10</td></tr> </table>			<b>Solids By Volume</b>	17				<b>Min</b>	<b>Max</b>	<b>Recommended</b>	<b>Wet Film Per Coat (microns)</b>			100	<b>Dry Film Per Coat (microns)</b>			17	<b>Recoat Time (min)</b>	2 hours			<b>Theoretical Spread Rate (m<sup>2</sup>/L)</b>		12	10
<b>Solids By Volume</b>	17																										
	<b>Min</b>	<b>Max</b>	<b>Recommended</b>																								
<b>Wet Film Per Coat (microns)</b>			100																								
<b>Dry Film Per Coat (microns)</b>			17																								
<b>Recoat Time (min)</b>	2 hours																										
<b>Theoretical Spread Rate (m<sup>2</sup>/L)</b>		12	10																								
Typical Properties Notes	DRYING TIME Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times.  Light foot traffic: 24 hours.																										

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> <li>Ensure surface is thoroughly clean and free from oil, grease, dirt and moss prior to application. Clean the surface with Feast Watson FLOORCLEAN as per the product instructions. For new concrete and aggregate pebbles allow the surface to cure for approximately 28 days then treat surface with a 10% solution (dilute) of Hydrochloric Acid. Apply Hydrochloric Acid using a brush or mop, allow the acid to remain on the surface for 15 minutes then flush off with clean water. Allow the surface to dry completely before applying PAVING &amp; SANDSTONE SEALER.</li> </ul>
Application Procedure And Equipment	<ul style="list-style-type: none"> <li>Stir thoroughly before and during use with a broad flat stirrer to maintain a uniform solution. Apply a minimum of two coats of PAVING &amp; SANDSTONE SEALER using either a Feast Watson Floor Finish Applicator, brush, fine mohair or wool roller.</li> </ul> <p>MAINTENANCE</p> <p>Monitor the surface for signs of loss of gloss or scratches. If an additional coat is required, clean using FLOORCLEAN. Apply one coat of PAVING &amp; SANDSTONE SEALER as per application instructions.</p>

## Health And Safety

<b>MSDS Number</b>	2606	<b>Using Safety Precautions</b>	RISK: Highly Flammable. Harmful by inhalation and in contact with skin. Irritating to respiratory system and skin. Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Avoid contact with skin and eyes and breathing in vapour or spray mist. Wear overalls, impervious gloves and safety glasses. Use only in well ventilated areas. If inhalation risk exists wear organic vapour/particulate respirator. This paint is flammable, so eliminate any sources of ignition.
<b>Health Effects</b>	<p>FIRST AID: For advice, contact a Poisons Information Centre (Phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor.</p> <p>SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical assistance.</p> <p>EYE: Rinse with plenty of running water. Seek medical help if irritation occurs.</p> <p>SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.</p> <p>INHALED: Remove from contaminated area.</p>	<b>Flammability</b>	This product is highly flammable.
<b>Protective Equipment</b>	Personal Protective Equipment: Wear eye protection, protective clothing and gloves, and if spraying wear a respirator with a combined vapour/particulate cartridge.	<b>Storage</b>	Keep out of reach of children.
<b>Disposal</b>	Do not pour leftover paint down the drain. Unwanted paint should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collections. Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.		

In the case of emergency, please call 1800 033 111

## Transport And Storage

<b>Pack A</b>	872-94657	<b>Shipment Name</b>	PAINTS
<b>Size</b>	20 Litres 10 Litres 4 Litres 1 Litre	<b>Weight</b>	18.3 Kg 9.2 Kg 3.7 Kg 917g
<b>Flash Point</b>	4C	<b>UN Number</b>	1263
<b>Dangerous Goods Class</b>	3	<b>Package Group</b>	I

### Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427