

AUFW00069 Feast Watson Proofint

Introduction

Part A
331-line

Description and Image

Feast Watson Proofint is a unique concentrated spirit based dye stain that allows the full clarity of the timber grain to show through after staining. Proofint is suitable for all interior timber, including furniture, doors, architraves and floors, and is suitable for use on all timber varieties including pine.

Proofint is a versatile stain that can be applied directly to the surface or diluted in Feast Watson Proofint Colour Reducer or Feast Watson Timber Primer. Additionally, Proofint can be added to Feast Watson Clear Varnish to create a one-step stain and varnish, or added to Feast Watson Liming Solution to achieve a range of soft pastel shades. Proofint colours can be mixed together to create your own custom shade or to achieve colour matches for your timber.



Features and Benefits

- Spirit- based stain
- Brush on-wipe off application
- Semi-transparent
- Add to turps-thinned products
- Quick drying
- Colour depth control
- Enhances natural grain and colour
- Can be used in most clear varnishes

Uses

Use Feast Watson Proofint Stain on all interior timbers, panelling, cupboards, furniture, wet areas, where it is desirable to stain then seal with a hard clear coating

Precautions and Limitations

Test colour on an off-cut or inconspicuous area prior to staining the whole job to ensure satisfaction with colour choice. Colour can be varied by mixing Proofint colours and adding Proofint Colour Reducer.


Note: The dwell time before wiping excess, and the finishing clear coat will impact the final colour.

Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Do not apply in temperatures under 10°C or above 35°C.

Performance Guide

Weather

For interior use only.

| Typical Properties | | | |
|---|---------------------------------|------------------------------------|----------------------|
| Colour 13 packaged colours | | | |
| Components 1 | | Number of Coats 1 or 2 | |
| Toxicity Lead free. Dry film is non-toxic and conforms to AS1647, Part 3. | | V.O.C. Level < 915g/L | |
| Meets GBCA V.O.C. Requirements? No | | | |
| Clean Up Description Clean brushes and other equipment using methylated spirits. When mixing Proofint with another coating, follow the cleaning instructions of the base coating. To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other. | | | |
| Application Methods  Brush Rag | | | |
| Application Conditions | | | |
| | Min | Max | Recommended |
| Theoretical Spread Rate (m ² /L) | <input type="text" value="10"/> | <input type="text" value="20"/> | <input type="text"/> |
| Typical Property Notes Coverage Approximately 10 - 20m ² per litre, depending on porosity of timber. Drying time Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Re-coat: 30 minutes when used neat; 1 hour when diluted. Top coat: 30 minutes when used neat; 12 hours when diluted. | | | |

Application Guide

Surface Preparation

New Timber

Sand to a smooth surface and remove all sanding dust before coating.

To achieve a super-smooth finish or if the timber grain is open or coarse, apply a coat of Feast Watson Sanding Sealer and sand back as per the directions.

Seal soft porous timbers, such as Pine, Meranti and Cedar with Feast Watson Timber Primer or another suitable primer to ensure even absorption into the timber.

Previously Coated Timber

Previously coated surfaces need to be sanded back to bare timber. Remove all sanding dust before staining.

Application Procedure and Equipment

Test colour on an off-cut or inconspicuous area prior to staining the whole job to ensure satisfaction with colour choice. Colour can be varied by mixing Prooftint colours and adding Prooftint Colour Reducer.

Note: The dwell time before wiping excess, and the finishing clear coat will impact the final colour.

For Small Areas

For small and detailed areas, apply Prooftint stain directly to the surface in the direction of the grain, by either brush or rag. Wipe off after 2-5 minutes depending on the depth of colour required.

Allow to dry, then seal with Feast Watson Clear Varnish as per the label instructions.

For Large Areas

For large areas including floors, dilute Prooftint in Prooftint Colour Reducer which will give more working time to distribute the stain evenly. Apply with a rag, brush or Feast Watson Floor Finish Applicator in the direction of the grain. Wipe off excess after a period of time determined by the desired colour intensity.

Allow to dry, then seal with an appropriate clear coating as per the label instructions, for example Feast Watson Floorclear or Feast Watson Timber Floor Wax.

Stain & Varnish Method

Add up to 10% Prooftint to Clean Varnish or Liming White Oil Based and apply as per the label instructions.

| Health and Safety | |
|--|----------|
| SDS Number Black DLXGHSEN003861 | SDS Link |
| SDS Number Black Japan DLXGHSEN003863 | SDS Link |
| SDS Number Brown Japan DLXGHSEN003863 | SDS Link |
| SDS Number Cedar DLXGHSEN003864 | SDS Link |
| SDS Number Elm DLXGHSEN003873 | SDS Link |
| SDS Number Golden Teak DLXGHSEN003872 | SDS Link |
| SDS Number Jarrah DLXGHSEN003869 | SDS Link |
| SDS Number Mahogany DLXGHSEN003865 | SDS Link |
| SDS Number Maple DLXGHSEN003870 | SDS Link |
| SDS Number Oak DLXGHSEN003866 | SDS Link |
| SDS Number Old Baltic DLXGHSEN003868 | SDS Link |
| SDS Number Teak Brown DLXGHSEN3871 | SDS Link |
| SDS Number Walnut DLXGHSEN003867 | SDS Link |
| <p>Using Safety Precautions Flammable liquid and vapour. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Keep out of reach of children. Read the label before opening or using. Keep away from all sources of ignition – No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and all other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist, vapours or spray. Use only outdoors or in a well ventilated area. Wear protective clothing, gloves, eye/ face protection and a suitable respirator as required. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before re-use. Wash hands, face and all exposed skin thoroughly after handling. Keep container tightly closed. Store locked up. Store in a well ventilated place, away from foodstuffs and oxidising agents. Keep cool. Do not empty into drains.</p> | |
| <p>Please refer to SDS Link. In case of emergency, please call 1800 220 770.</p> | |

| Transport and Storage | |
|---|---|
| Pack A 331-line | |
| Size: <input type="text" value="50ml 250ml 1L 2L"/> | Weight: <input type="text" value="0.10Kg 0.31Kg 1.09Kg 2.03Kg"/> |
| <p>Please refer to the Safety Data Sheet for full safety, health and transportation information.</p> | |

Further Information

Product page

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.