



Zero Track

High-tech LED lighting system for interior architecture

Description


This new 24V system for surface mounted installation is characterized by its diminutive dimensions, providing a minimalist aesthetic which is perfect for many architectural spaces. The extruded aluminum track is available up to 2 meters long, and available in white, black, deep brown, bronze and chrome finishes. Zero Track is especially useful for residential applications, and concrete ceilings where recessed lighting cannot be installed. Easy to specify, easy to install and with a large variety of elegant spots, pendants, and area light fixtures designed by Jorge Herrera and Piero Lissoni.

Lamp

System Lamp Type	LED
Color Temperature	2700K, 3000K
Color Rendering	CRI90
Application	General Lighting



Surface Installation



Physical

Material	Aluminum
Ingress Protection Rating	IP20
Finishes	☐ 40 = White ☐ 14 = Black ☐ 05 = Chrome ☐ CZ = Bronze ☐ 18 = Deep brown
Installation type	Surface
Environment	Indoor
Field cuttable	Yes

Light Modules



Certifications



Photometrics

For current IES files please visit arch.flosusa.com

Warranty

2 years from date of sale.

Electrical & Control

Driver location	Remote
Driver Input Voltage	120V-277V
Driver Output Voltage	24V
Maximum Driver Wattage	96W
Maximum Current	4A
Control	Non-Dimmable



Zero Track

High-tech LED lighting system for interior architecture

Notes

Wattage per linear foot is dependent upon quantity and type of light modules used.

Contractor to supply wire from driver to luminaire. Drivers should be installed in a suitable electrical enclosure (by others), and an accessible location.

The surface mounted track is directly screwed to any surface. FLOS provides the mounting hardware.

2 options in term of power supply:


Remote power supply

Surface mounted canopy directly connected to the track. Includes a Jbox cover plate. Track and Surface mounted canopy need to be completely aligned.

The maximum length that can be fed with a single 96W driver is 19'-6", however voltage drop may limit actual lengths to shorter runs. Consult factory for specific application assistance.

3500K and other CCTs are available but not cataloged. Consult factory.

Surface Installation



Light Modules



Certifications



Photometrics

For current IES files please visit arch.
flosusa.com

Warranty

2 years from date of sale.

How to Specify

A. Select and position corners

1. 90deg Corner - Connect sections on flat surfaces
2. Inner Corner - Connect sections wall/wall, wall/ceiling)

B. Fill lengths between corners with Linear Housings

Available section lengths are 3.3', and 6.7'. Profile can be easily cut on site to exact length and joined together with other track sections.

C. Drivers

Quantity of drivers determined by total wattage or light elements in section (total maximum possible per linear foot is 29W).

Maximum driver distance is 15'. Locate drivers nearby.

D. Select Spot heads

Individual Spots are Find Me zero, Find Me 1, Find Me 2, Find Me 1 Suspension, Atom 90, Atom 120 and Atom 200.

Zero Track

High-tech LED lighting system for interior architecture


Profiles

39.4" [1 m] Profile

Indoor Track for surface mounted installations (ceiling or wall). To be fixed with specific screw plugs that come with the track. All accessories need to be order separately.

Part Number:

- 06.2500.40
06.2500.05
06.2500.14
06.2500.CZ
06.2500.18




78.7" [2 m] Profile

Indoor Track for surface mounted installations (ceiling or wall). To be fixed with specific screw plugs that come with the track. All accessories need to be order separately.

Part Number:

- 06.2501.40
06.2501.05
06.2501.14
06.2501.CZ
06.2501.18




118.1" [3 m] Profile


Indoor Track for surface mounted installations (ceiling or wall). To be fixed with specific screw plugs that come with the track. All accessories need to be order separately.

Part Number:

- 06.2502.40
06.2502.05
06.2502.14
06.2502.CZ
06.2502.18



How to specify



Zero Track

High-tech LED lighting system for interior architecture


Connectors

Feed unit for remote power supply unit

Power cable inserting is possible both from the top and the side.

Part Number:

- 06.2540.40
06.2540.14
06.2540.CZ
06.2540.18




Feed intermediate connector.

Upper feeding cable entry.

Part Number:


- 06.2541.40
06.2541.14
06.2541.CZ
06.2541.18



Intermediate connector

Part Number:

- 06.2506.40
06.2506.14




Accessories

End Cap Kit

Part Number:

- 06.2509.40
06.2509.14
06.2509.CZ
06.2509.18




Stopper

For fixing luminaires in vertical track installations.

Part Number:

- 08.0630.40
08.0630.14



Zero Track

High-tech LED lighting system for interior architecture


Corners

Flat Corner 90°

Can be powered. It has a rear space for the supply connection.

Part Number:

- ☐ 06.2542.40
- ☐ 06.2542.14
- ☐ 06.2542.CZ
- ☐ 06.2542.18




Ceiling/wall - wall/wall inner corner

Can be powered. It has two spaces for the supply connection located on each side at the rear.

Part Number:

- ☐ 06.2543.40
- ☐ 06.2543.14
- ☐ 06.2543.CZ
- ☐ 06.2543.18



Interior ceiling/ceiling-wall/wall curve.

Can be powered via connections on the back.

Part Number:

- ☐ 06.2544.40
- ☐ 06.2544.14
- ☐ 06.2544.CZ
- ☐ 06.2544.18




T-shaped connector

Can be powered via connections on the back.

Part Number:

- ☐ 06.2545.40
- ☐ 06.2545.14
- ☐ 06.2545.CZ
- ☐ 06.2545.18




Cross-shaped connector

Can be powered via connections on the back.

Part Number:

- ☐ 06.2546.40
- ☐ 06.2546.14
- ☐ 06.2546.CZ
- ☐ 06.2546.18



Zero Track


High-tech LED lighting system for interior architecture

Required Drivers

LED Driver, 24VDC, 96W, Non-Dimming,
120-277V

Part Number:


LEDSB96W24V-NDM-D1



LED Driver, 24VDC, 60W, Non-Dimming,
120-277V

Part Number:

LEDSB60W24V-NDM-D1








Zero Track

High-tech LED lighting system for interior architecture

Find Me 0

LED accent lighting module to be installed in the Zero Track system. Electronic DC/DC converter inside the fixture body. The maximum number of luminaries that can be feeded with the same power supply is 13. Honeycomb and cross baffle comes standard with the fixture. IP20



CCT *	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Photometric
2700	90	300	169	3.5W	15°	09.3801	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	 Beam Angle: 15° h(m) E(lx) D(m) 1 1303 0.26 2 326 0.52 3 145 0.77 4 81 1.03 5 52 1.29 Luminous flux luminaire 169 lm
3000	90	325	183	3.5W	15°	09.3800	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	 Beam Angle: 15° h(m) E(lx) D(m) 1 1412 0.26 2 353 0.52 3 157 0.77 4 88 1.03 5 56 1.29 Luminous flux luminaire 183 lm
2700	90	300	163	3.5W	20°	09.3803	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	 Beam Angle: 20° h(m) E(lx) D(m) 1 1059 0.36 2 265 0.72 3 118 1.08 4 66 1.44 5 42 1.80 Luminous flux luminaire 163 lm
3000	90	325	177	3.5W	20°	09.3802	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	 Beam Angle: 20° h(m) E(lx) D(m) 1 1151 0.36 2 288 0.72 3 128 1.08 4 72 1.44 5 46 1.80 Luminous flux luminaire 177 lm

* Consult factory for other available CCT





Zero Track

High-tech LED lighting system for interior architecture

Find Me 1

LED accent lighting module to be installed in the Zero Track system. Electronic DC/DC converter inside the fixture body. The maximum number of luminaries that can be feeded with the same power supply is 9. Honeycomb and cross baffle comes standard with the fixture. IP20



CCT *	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Photometric																	
2700	90	450	309	5.5W	14°	09.3812	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown  Beam Angle: 14°<table><tr><th>h(m)</th><th>E(lx)</th><th>D(m)</th></tr><tr><td>1</td><td>4168</td><td>0.24</td></tr><tr><td>2</td><td>1042</td><td>0.48</td></tr><tr><td>3</td><td>463</td><td>0.72</td></tr><tr><td>4</td><td>261</td><td>0.95</td></tr><tr><td>5</td><td>167</td><td>1.19</td></tr></table>Luminous flux luminaire 309 lm	h(m)	E(lx)	D(m)	1	4168	0.24	2	1042	0.48	3	463	0.72	4	261	0.95	5	167	1.19
h(m)	E(lx)	D(m)																							
1	4168	0.24																							
2	1042	0.48																							
3	463	0.72																							
4	261	0.95																							
5	167	1.19																							
3000	90	485	314	5.5W	14°	09.3810	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown  Beam Angle: 14°<table><tr><th>h(m)</th><th>E(lx)</th><th>D(m)</th></tr><tr><td>1</td><td>4193</td><td>0.24</td></tr><tr><td>2</td><td>1048</td><td>0.49</td></tr><tr><td>3</td><td>466</td><td>0.73</td></tr><tr><td>4</td><td>262</td><td>0.97</td></tr><tr><td>5</td><td>168</td><td>1.21</td></tr></table>Luminous flux luminaire 314 lm	h(m)	E(lx)	D(m)	1	4193	0.24	2	1048	0.49	3	466	0.73	4	262	0.97	5	168	1.21
h(m)	E(lx)	D(m)																							
1	4193	0.24																							
2	1048	0.49																							
3	466	0.73																							
4	262	0.97																							
5	168	1.21																							
2700	90	450	186	5.5W	20°	09.3813	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown  Beam Angle: 20°<table><tr><th>h(m)</th><th>E(lx)</th><th>D(m)</th></tr><tr><td>1</td><td>1238</td><td>0.35</td></tr><tr><td>2</td><td>310</td><td>0.70</td></tr><tr><td>3</td><td>138</td><td>1.06</td></tr><tr><td>4</td><td>77</td><td>1.41</td></tr><tr><td>5</td><td>50</td><td>1.76</td></tr></table>Luminous flux luminaire 186 lm	h(m)	E(lx)	D(m)	1	1238	0.35	2	310	0.70	3	138	1.06	4	77	1.41	5	50	1.76
h(m)	E(lx)	D(m)																							
1	1238	0.35																							
2	310	0.70																							
3	138	1.06																							
4	77	1.41																							
5	50	1.76																							
3000	90	485	193	5.5W	20°	09.3811	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown  Beam Angle: 20°<table><tr><th>h(m)</th><th>E(lx)</th><th>D(m)</th></tr><tr><td>1</td><td>1285</td><td>0.35</td></tr><tr><td>2</td><td>321</td><td>0.70</td></tr><tr><td>3</td><td>143</td><td>1.06</td></tr><tr><td>4</td><td>80</td><td>1.41</td></tr><tr><td>5</td><td>51</td><td>1.76</td></tr></table>Luminous flux luminaire 193 lm	h(m)	E(lx)	D(m)	1	1285	0.35	2	321	0.70	3	143	1.06	4	80	1.41	5	51	1.76
h(m)	E(lx)	D(m)																							
1	1285	0.35																							
2	321	0.70																							
3	143	1.06																							
4	80	1.41																							
5	51	1.76																							

* Consult factory for other available CCT

Zero Track

High-tech LED lighting system for interior architecture

Find Me 2



CCT *	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Photometric
2700	90	650	479	10.5W	10°	09.3862	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	Beam Angle: 10° h(m) E(lx) D(m) 1 9244 0.18 2 2311 0.35 3 1027 0.53 4 578 0.70 5 370 0.88 Luminous flux luminaire 479 lm
3000	90	700	531	10.5W	10°	09.3860	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	Beam Angle: 10° h(m) E(lx) D(m) 1 10249 0.18 2 2562 0.35 3 1139 0.53 4 641 0.70 5 410 0.88 Luminous flux luminaire 531 lm
2700	90	650	441	10.5W	19°	09.3863	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	Beam Angle: 19° h(m) E(lx) D(m) 1 1991 0.34 2 498 0.67 3 221 1.01 4 124 1.34 5 80 1.68 Luminous flux luminaire 441 lm
3000	90	700	489	10.5W	19°	09.386 1	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	Beam Angle: 19° h(m) E(lx) D(m) 1 2208 0.34 2 552 0.67 3 245 1.01 4 138 1.34 5 88 1.68 Luminous flux luminaire 489 lm
2700	90	650	364	10.5W	32°	09.3865	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	Beam Angle: 32° h(m) E(lx) D(m) 1 722 0.57 2 180 1.15 3 80 1.72 4 45 2.29 5 29 2.87 Luminous flux luminaire 364 lm
3000	90	700	404	10.5W	32°	09.3864	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	Beam Angle: 32° h(m) E(lx) D(m) 1 800 0.57 2 200 1.15 3 89 1.72 4 50 2.29 5 32 2.87 Luminous flux luminaire 404 lm


* Consult factory for other available CCT

Zero Track

High-tech LED lighting system for interior architecture.

Find Me 1 Suspension

LED accent lighting module to be installed in the Zero Track system. Electronic DC/DC converter inside the fixture body. Module controlled by PMW with 0-10V dimmer or controller. The maximum number of luminaries that can be feeded with the same power supply is 9.



OCT *	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Photometric
2700	90	450	309	5.5W	14°	09.3822	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	90° 60° 30° 4168 cd Luminous flux luminaire 309 lm Beam Angle: 14° h(m) E(lx) D(m) 1 4168 0.24 2 1042 0.48 3 463 0.72 4 261 0.95 5 167 1.19
3000	90	485	314	5.5W	14°	09.3820	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	90° 60° 30° 4193 cd Luminous flux luminaire 314 lm Beam Angle: 14° h(m) E(lx) D(m) 1 4193 0.24 2 1048 0.49 3 466 0.73 4 262 0.97 5 168 1.21
2700	90	450	186	5.5W	20°	09.3823	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	90° 60° 30° 1238 cd Luminous flux luminaire 186 lm Beam Angle: 20° h(m) E(lx) D(m) 1 1238 0.35 2 310 0.70 3 138 1.06 4 77 1.41 5 50 1.76
3000	90	485	193	5.5W	20°	09.3821	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	90° 60° 30° 1285 cd Luminous flux luminaire 193 lm Beam Angle: 20° h(m) E(lx) D(m) 1 1285 0.35 2 321 0.70 3 143 1.06 4 80 1.41 5 51 1.76

* Consult factory for other available CCT

Zero Track

High-tech LED lighting system for interior architecture.

Atom 90

LED accent lighting module to be installed in the Zero Track system. Electronic DC/DC converter inside the fixture body. The maximum number of luminaires that can be fedded with the same power supply is 9. Honeycomb and cross baffle comes standard with the fixture. IP20



CCT *	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Photometric																		
2700	90	450	224	5.5W	14°	09.3831	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	90° 60° 30° 2558 cd 30° 60° 90° Luminous flux luminaire 224 lm Beam Angle: 14° <table><tr><th>h(m)</th><th>E(lx)</th><th>D(m)</th></tr><tr><td>1</td><td>2558</td><td>0.25</td></tr><tr><td>2</td><td>640</td><td>0.51</td></tr><tr><td>3</td><td>284</td><td>0.76</td></tr><tr><td>4</td><td>160</td><td>1.02</td></tr><tr><td>5</td><td>102</td><td>1.27</td></tr></table>	h(m)	E(lx)	D(m)	1	2558	0.25	2	640	0.51	3	284	0.76	4	160	1.02	5	102	1.27
h(m)	E(lx)	D(m)																								
1	2558	0.25																								
2	640	0.51																								
3	284	0.76																								
4	160	1.02																								
5	102	1.27																								
3000	90	485	247	5.5W	14°	09.3830	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	90° 60° 30° 2832 cd 30° 60° 90° Luminous flux luminaire 247 lm Beam Angle: 14° <table><tr><th>h(m)</th><th>E(lx)</th><th>D(m)</th></tr><tr><td>1</td><td>2832</td><td>0.25</td></tr><tr><td>2</td><td>708</td><td>0.51</td></tr><tr><td>3</td><td>315</td><td>0.76</td></tr><tr><td>4</td><td>177</td><td>1.02</td></tr><tr><td>5</td><td>113</td><td>1.27</td></tr></table>	h(m)	E(lx)	D(m)	1	2832	0.25	2	708	0.51	3	315	0.76	4	177	1.02	5	113	1.27
h(m)	E(lx)	D(m)																								
1	2832	0.25																								
2	708	0.51																								
3	315	0.76																								
4	177	1.02																								
5	113	1.27																								
2700	90	450	217	5.5W	21°	09.3833	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	90° 60° 30° 1362 cd 30° 60° 90° Luminous flux luminaire 217 lm Beam Angle: 21° <table><tr><th>h(m)</th><th>E(lx)</th><th>D(m)</th></tr><tr><td>1</td><td>1362</td><td>0.37</td></tr><tr><td>2</td><td>341</td><td>0.73</td></tr><tr><td>3</td><td>151</td><td>1.10</td></tr><tr><td>4</td><td>85</td><td>1.47</td></tr><tr><td>5</td><td>54</td><td>1.84</td></tr></table>	h(m)	E(lx)	D(m)	1	1362	0.37	2	341	0.73	3	151	1.10	4	85	1.47	5	54	1.84
h(m)	E(lx)	D(m)																								
1	1362	0.37																								
2	341	0.73																								
3	151	1.10																								
4	85	1.47																								
5	54	1.84																								
3000	90	485	240	5.5W	21°	09.3832	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	90° 60° 30° 1508 cd 30° 60° 90° Luminous flux luminaire 240 lm Beam Angle: 21° <table><tr><th>h(m)</th><th>E(lx)</th><th>D(m)</th></tr><tr><td>1</td><td>1508</td><td>0.37</td></tr><tr><td>2</td><td>377</td><td>0.73</td></tr><tr><td>3</td><td>168</td><td>1.10</td></tr><tr><td>4</td><td>94</td><td>1.47</td></tr><tr><td>5</td><td>60</td><td>1.84</td></tr></table>	h(m)	E(lx)	D(m)	1	1508	0.37	2	377	0.73	3	168	1.10	4	94	1.47	5	60	1.84
h(m)	E(lx)	D(m)																								
1	1508	0.37																								
2	377	0.73																								
3	168	1.10																								
4	94	1.47																								
5	60	1.84																								


* Consult factory for other available CCT





Zero Track

High-tech LED lighting system for interior architecture.

Atom 120

LED accent lighting module to be installed in the Zero Track system. Electronic DC/DC converter inside the fixture body. The maximum number of luminaries that can be feeded with the same power supply is 9. Honeycomb and cross baffle comes standard with the fixture. IP20



CCT *	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Photometric
2700	90	635	433	8W	14°	09.3841	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	 Beam Angle: 14° h(m) E(lx) D(m) 1 5843 0.24 2 1461 0.48 3 649 0.72 4 365 0.95 5 234 1.19 5843 cd Luminous flux luminaire 433 lm
3000	90	680	440	8W	14°	09.3840	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	 Beam Angle: 14° h(m) E(lx) D(m) 1 5878 0.24 2 1469 0.49 3 653 0.73 4 367 0.97 5 235 1.21 5878 cd Luminous flux luminaire 440 lm
2700	90	635	364	8W	20°	09.3843	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	 Beam Angle: 20° h(m) E(lx) D(m) 1 2557 0.35 2 639 0.70 3 284 1.06 4 160 1.41 5 102 1.76 2557 cd Luminous flux luminaire 364 lm
3000	90	680	373	8W	20°	09.3842	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown	 Beam Angle: 20° h(m) E(lx) D(m) 1 2624 0.35 2 656 0.70 3 292 1.06 4 164 1.41 5 105 1.76 2624 cd Luminous flux luminaire 373 lm


* Consult factory for other available CCT

Zero Track

High-tech LED lighting system for interior architecture.

Atom 200

LED accent lighting module to be installed in the Zero Track system. Electronic DC/DC converter inside the fixture body. Module controlled by PMW with 0-10V dimmer or controller. The maximum number of luminaries that can be feeded with the same power supply is 4.



CCT *	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Spread	Part Number	Finish	Photometric											
2700	90	1050	395	10.5W	110°	09.3851	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown <table><tr><th>E(lx)</th><th>D(m)</th></tr><tr><td>1</td><td>145 2.86</td></tr><tr><td>2</td><td>36 5.73</td></tr><tr><td>3</td><td>16 8.59</td></tr><tr><td>4</td><td>9 11.45</td></tr><tr><td>5</td><td>5 14.32</td></tr></table> Luminous flux luminaire 395 lm	E(lx)	D(m)	1	145 2.86	2	36 5.73	3	16 8.59	4	9 11.45	5	5 14.32
E(lx)	D(m)																		
1	145 2.86																		
2	36 5.73																		
3	16 8.59																		
4	9 11.45																		
5	5 14.32																		
3000	90	1150	424	10.5W	110°	09.3850	40A = White 05A = Chrome 14A = Black CZA = Bronze 18A = Deep brown <table><tr><th>E(lx)</th><th>D(m)</th></tr><tr><td>1</td><td>156 2.86</td></tr><tr><td>2</td><td>39 5.73</td></tr><tr><td>3</td><td>17 8.59</td></tr><tr><td>4</td><td>10 11.45</td></tr><tr><td>5</td><td>6 14.32</td></tr></table> Luminous flux luminaire 424 lm	E(lx)	D(m)	1	156 2.86	2	39 5.73	3	17 8.59	4	10 11.45	5	6 14.32
E(lx)	D(m)																		
1	156 2.86																		
2	39 5.73																		
3	17 8.59																		
4	10 11.45																		
5	6 14.32																		

* Consult factory for other available CCT