FLOS
ARCHITECTURAL

Fixture Type .....

Job Name .....

UT Spot D86 Track

Track Mounted Directional Accent

Description

The UT Spot is a family of high output indoor track lights suitable for any application, from museum exhibitions to commercial premises and offices or residential environments. Available up to 3770 lumens each, the UT Spot is line voltage and houses its driver in a discreet small box that integrates with the track, giving it a sleek modern look.

A luminaire for indoor use to be mounted on three phase track, available in LED technology light sources and in dimmable or not dimmable versions.

The optical housing of the luminaire is manufactured in high-pressure injected aluminum, with white or black finishes.

Lamps

LED ARRAY : Citizen
33W, 3770lm, 3000K, CRI 80
33W, 3100lm, 3000K, CRI 90
33W, 3250lm, 4000K, CRI 90

Delivered lumen from 1990 lm up to 2646lm

Construction

Fixture body is high pressure injected aluminum.

All optics are made of aluminum with specular finish.

Photometrics

For current IES files please visit architectural.flosusa.com

Finish

☐ 30 White ■ 14 Black

Electrical

Fixture is constant current, low voltage LED with integral power supply.

Track heads are designed for use with standard three circuit track.

Fixture is 33 watts.

Notes

Maximum tilt angle 90°.

Maximum rotation 365°.

Beam spreads available in 12°, 23° and 40°.

Track head wattage is model dependant.

Listings: UL Listed, IP20 dry location only, Class 2

Warranty

2 years from date of sale.

F L O S . U S A
110 York Street
Brooklyn, NY 11201
(718).875.3472

For more information contact your representative or go to architectural.FlosUSA.com.
©2019 Specifications and dimensions subject to change without notice. Issued 12.25.2019

c UL us LISTED

FLOS
ARCHITECTURAL

Fixture Type .....

Job Name .....

UT Spot D86 Track

Track Mounted Directional Accent

How to Specify

0	9	.	4	8	8	0	.	1	4	A	9	V
Part Number								Finish		Dimming Protocol or Power Supply		

How to Specify

ex. 09.4880.30A90

Item Number	Beam Angle	CCT	CRI	Wattage	Initial lumens	Finish	Power Suply
09.4880	12º	3000K	80	33W	3770lm	☐ 30 = White ■ 14 = Black	A90= Integral non-dimming driver, 40W, 120-277V A9V= Integral ELV dimming driver, 36W, 120
09.4882	23º						
09.4884	40º						
09.4886	12º	3000K	90	33W	3100lm	☐ 30 = White ■ 14 = Black	A90= Integral non-dimming driver, 40W, 120-277V A9V= Integral ELV dimming driver, 36W, 120V
09.4887	23º						
09.4888	40º						
09.4881	12º	4000K	90	33W	3250lm	☐ 30 = White ■ 14 = Black	A90= Integral non-dimming driver, 40W, 120-277V A9V= Integral ELV dimming driver, 36W, 120V
09.4883	23º						
09.4885	40º						

F L O S . U S A
110 York Street
Brooklyn, NY 11201
(718).875.3472

For more information contact your representative or go to architectural.FlosUSA.com.
©2019 Specifications and dimensions subject to change without notice. Issued 12.25.2019

c UL us LISTED

FLOS
ARCHITECTURAL

Fixture Type .....
Job Name .....

UT Spot D86 Track

Track Mounted Directional Accent

Optional Accesories

Image	QTY	Item Number	Description
		08.8410.00	Holding ring
		08.8411.00	Cross baffle
		08.8163.68	Elliptical lens (to use with the holding ring)
		08.8175.68	Flood lens (to use with the holding ring)
		08.8495.14	Honeycomb anti-glare louvre (to use with the holding ring)

Track Required

Image	Description
	See Spec-sheet for Global 3c-track Contact FLOS sales agent for configuration of layout and specification information

F L O S . U S A
110 York Street
Brooklyn, NY 11201
(718).875.3472

For more information contact your representative or go to architectural.FlosUSA.com.
©2019 Specifications and dimensions subject to change without notice. Issued 12.25.2019

C UL US LISTED