FLOS
ARCHITECTURAL

Fixture Type .....

Job Name .....

UT Spot D57 Track

Track Mounted Directional Accent

Description

The UT Spot is a family of high output indoor track lights suitable for any application, from museum exhibitions to commercial premises and offi es or residential environments. Available up to 2150 lumens each, the UT Spot is line voltage and houses its driver in a discreet small box that integrates with the track, giving it a sleek modern look.

A luminaire for indoor use to be mounted on three phase track, available in LED technology light sources and in dimmable or not dimmable versions.

The optical housing of the luminaire is manufactured in high-pressure injected aluminium, with white or black finish s.

Lamps

LED ARRAY : Citizen
18W, 2150lm, 3000K, CRI 80
18W, 1780lm, 3000K, CRI 90
18W, 1900lm, 4000K, CRI 90

Delivered lumen from 1471 lm up to 2145lm

Photometrics

For current IES files please visit architectural.flosusa.com

Warranty

2 years from date of sale.

Finish

☐ 30 White ■ 14 Black

Construction

Fixture body is high pressure injected aluminium.

All optics are made of aluminium with specular finish

Electrical

Fixture is constant current, low voltage LED with integral power supply.

Track heads are designed for use with standard three circuit track.

Fixture is 18 watts.

Notes

Maximum tilt angle 90°.

Maximum rotation 365°.

Beam spreads available in 12°, 23° and 40°.

Track head wattage is model dependant.

Listings: UL Listed, IP20 dry location only, Class 2

F L O S . U S A
110 York Street
Brooklyn, NY 11201
(718).875.3472

For more information contact your representative or go to architectural.FlosUSA.com.
©2019 Specifications and dimensions subject to change without notice. Issued 12.25.2019

C UL US LISTED

FLOS
ARCHITECTURAL

Fixture Type .....

Job Name .....

UT Spot D57 Track

Track Mounted Directional Accent

How to Specify

0	9	.	4	4	8	0	.	1	4	A	9	V
Part Number								Finish		Dimming Protocol or Power Supply		

How to Specify

ex. 09.4480.30A9V

Part Number	Beam Angle	CCT	CRI	Wattage	Initial lumens	Finish	Dimming Protocol
09.4480	12º	3000K	80	18W	2150lm	☐ 30 = White ■ 14 = Black	A90= Integral non-dimming driver, 120-277V A9V= Integral ELV dimming driver, 120V
09.4482	23º						
09.4484	40º						
09.4486	12º	3000K	90	18W	1780lm	☐ 30 = White ■ 14 = Black	A90= Integral non-dimming driver, 120-277V A9V= Integral ELV dimming driver, 120V
09.4487	23º						
09.4488	40º						
09.4481	12º	4000K	90	18W	1900lm	☐ 30 = White ■ 14 = Black	A90= Integral non-dimming driver, 120-277V A9V= Integral ELV dimming driver, 120V
09.4483	23º						
09.4485	40º						

F L O S . U S A
110 York Street
Brooklyn, NY 11201
(718).875.3472

For more information contact your representative or go to architectural.FlosUSA.com.
©2019 Specifications and dimensions subject to change without notice. Issued 12.25.2019

c UL us LISTED

FLOS
ARCHITECTURAL

Fixture Type .....
Job Name .....

UT Spot D57 Track

Track Mounted Directional Accent

Optional Accesories

Image	QTY	Item Number	Description
		08.8429.00	Cross Baffl
		08.8431.00	Elliptical lens (to use with the holding ring)
		08.8432.00	Flood lens (to use with the holding ring)
		08.8428.00	Honeycomb anti-glare louvre
		08.0526.00	Snoot shielding cone

Track Required

Image	Description
	See Spec-sheet for Global 3c-track Contact FLOS sales agent for configuration of layout and specification information

F L O S . U S A
110 York Street
Brooklyn, NY 11201
(718).875.3472

For more information contact your representative or go to architectural.FlosUSA.com.
©2019 Specifications and dimensions subject to change without notice. Issued 12.25.2019

C UL US LISTED