FLOS
ARCHITECTURAL

Fixture Type .....

Job Name .....

UT Spot Wall-Washer D86 Track

Track Mounted Directional Accent

Description

The UT Spot is a family of high output indoor track lights suitable for any application, from museum exhibitions to commercial premises and offices or residential environments. Available up to 3770 lumens each, the UT Spot is line voltage and houses its driver in a discreet small box that integrates with the track, giving it a sleek modern look.

A light fixture for indoor use to be mounted on three phase track, available in LED technology light sources and in dimmable or no dimmable versions.

The optical housing of the luminaire is manufactured in high-pressure injected aluminum, with white or black finishes.

Lamps

LED ARRAY : Citizen
33W, 3770lm, 3000K, CRI80
33W, 3100lm, 3000K, CRI90
33W, 3250lm, 4000K, CRI90

Photometrics

For current IES files please visit architectural.flos.com

Construction

Fixture body is high pressure injected aluminum.

All optics are made of aluminum with specular finish.

Finish

☐ 30 White ■ 14 Black

Electrical

Fixture is constant current, low voltage LED with integral power supply.

Track heads are designed for use with standard three circuit track.

Fixture is 33 watts.

Notes

Maximum tilt angle 90°.

Maximum rotation 365°.

Track head wattage is model dependant.

Listings: UL Listed, IP20 dry location only, Class 2.

Warranty

2 years from date of sale.

F L O S . U S A
110 York Street
Brooklyn, NY 11201
(718).875.3472

For more information contact your representative or go to architectural.FlosUSA.com.
©2019 Specifications and dimensions subject to change without notice. Issued 12.25.2019

C UL US LISTED

FLOS
ARCHITECTURAL

Fixture Type .....

Job Name .....

UT Spot Wall-Washer D86 Track

Track Mounted Directional Accent

How to Specify

0	9	.	4	9	5	1	.	1	4	A	9	V
Part Number								Finish		Dimming Protocol or Power Supply		

How to Specify

ex. 09.4951.30A90

QTY	Item Number	CCT	CRI	Wattage	Initial lumens	Finish	Power Supply
	09.4951	3000K	80	33W	3770lm	☐ 30 = White ■ 14 = Black	A90 = Integral non-dimming driver, 120V-277V A9V = Integral ELV dimming driver, 120V
	09.4954	3000K	90	33W	3100lm	☐ 30 = White ■ 14 = Black	A90 = Integral non-dimming driver, 120V-277V A9V = Integral ELV dimming driver, 120V
	09.4957	4000K	90	33W	3250lm	☐ 30 = White ■ 14 = Black	A90 = Integral non-dimming driver, 120V-277V A9V = Integral ELV dimming driver, 120V

Track Required

Image	Description
	See Spec-sheet for Global 3c-track Contact FLOS sales agent for configuration of layout and specification information

F L O S . U S A
110 York Street
Brooklyn, NY 11201
(718).875.3472

For more information contact your representative or go to architectural.FlosUSA.com.

©2019 Specifications and dimensions subject to change without notice. Issued 12.25.2019

C UL US LISTED