



## Find Me Zero

Ceiling Recessed Trimmed / Trimless Adjustable Spotlight


### Description

Hide-and-go-seek brought to light. The versatile Find Me is a tiny semi-recessed downlight hidden in the ceiling until otherwise sought. With a simple pull, the downlight can extend below the ceiling and transform into a refined cylindrical monopoint. This diminutive yet powerful luminaire is endlessly versatile and can tilt 90 degrees and rotate 360 degrees. Deep matte black snoot maximizes cut off and reduces glare. The Find Me line is available in a single version with or without trim and in a pendant version.

### Lamp

Lamp Type	LED
Wattage	3W
Output Nominal	300lm, 325lm
Color Temperature	2700K, 3000K 3500K* (See Notes)
Color rendering	CRI 90

### Dimensions



### Optical

Beam Angle	26°
Lighting Type	Direct
Light Distribution	Symmetric

### Physical

Material	Aluminum
Aiming	Adjustable
Weight	0.3 Lbs
Ingress Protection Rating	IP20
Maximum tilt Angle	70°
Rotation	360°

### Finishes

Painted lacquer

30 White     06 Chrome     14 Black



### Certifications



### Photometrics

For current IES files please visit [arch.flosusa.com](http://arch.flosusa.com)

### Warranty

2 years from date of sale.

Installation type	Ceiling Trim / Trimless
Environment	Indoor
Minimum Plenum height	5.5"
Maximum Ceiling thickness	1.18"



## Find Me Zero

Ceiling Recessed Trimmed / Trimless Adjustable Spotlight


### Electrical & Control

Driver location:	Remote
Driver Input Voltage	120V-277V
Fixture Vf	13V
Current mA	250mA
Control	Control: 0-10V

### Performance


Maximum delivered output	From 170lm to 189lm
Efficacy	63lm/W

### Dimensions



### Notes

- Integral LED is not field replaceable.
- IC-rated downlight for direct insulation contact.
- Fixture is constant Current Low Voltage LED, Class 2.
- Just 1 accessory can be install at the time. For filter options contact Flos.
- Wiring suitable for plenum spaces.
- 3500K available, but not cataloged. Consult factory for additional color temperatures.



### Certifications



### Photometrics

For current IES files please visit [arch.flosusa.com](http://arch.flosusa.com)


### Warranty

2 years from date of sale.

## Find Me Zero

Ceiling Recessed Trimmed / Trimless Adjustable Spotlight

### How to specify




### How to Specify


ex. 09.3780.30A9S + SP40W250MA-10V-A01

Part Number	CCT	CRI	Initial Lumens	Delivered Lumens	Watts	Beam Angle	Finish	Dimming Protocol
09.3780	3000	90	600	182	3W	26°	<input type="checkbox"/> 30 = White <input checked="" type="checkbox"/> 14 = Black <input type="checkbox"/> 06 = Chrome	A9S = Remote Power Supply
09.3781	2700	90	560	189	3W	26°		

### Photometrics



2700K



3000K

## Find Me Zero

Ceiling Recessed Trimmed / Trimless Adjustable Spotlight

### Required Splice Box

Splice Box UL 7"x3-5/8"x1-1/4", UL. With Driver Programmed to 250mA , 25W, 0-10V Dimmable, 120-277V / Required for Canada

SP25W250MA-10V-A01

