



In Vitro Bollard 3


Bollard Outdoor Light Designed by Philippe Starck

Description

Lighting outdoor collection with diffuse light for exterior ground, wall and ceiling/ suspension installation. Integral opalescent diffuser and external protection in transparent borosilicate glass. The structure is made of die-cast and extruded aluminum treated with a chemical conversion process for effective resistance to atmospheric agents. The body is powder coated and comes in various finishes. Integrated LED light source with Edge Lighting optical technology to guarantee perfect light uniformity. Integral 120V ON/OFF or 0-10V dimmable electrical power supply. The bollard version can be installed on any floor with anchors. Required Box accessory for concrete installation on ground to be order separately.



Dimensions



Certifications



Photometrics

For current IES files please visit
arch.flosusa.com

Warranty

2 years from date of sale.

Lamp

Lamp Type	LED - Edge Lighting
Wattage	11W
Output Nominal	1150lm, 1230lm
Color Temperature	2700K, 3000K
Color rendering	CRI 80

Optical

Beam Angle	111°
Lighting Type	Direct
Light Distribution	Symmetric

Physical

Material	Aluminum / Glass
Aiming	Fixed
Weight	4.4 Lbs
Ingress Protection Rating	IP66
Finishes	Painted lacquer

01 White	33 Anthracite	30 Black	18 Deep Brown
12 Forest Green	25 Terracotta	13 Pale Green	

Installation type	Ground
Environment	Outdoor, Wet location
Impact protection	K10 Top / IK03 Glass



In Vitro Bollard 3

Bollard Outdoor Light Designed by Philippe Starck

Electrical & Control

Voltage	120V
Control	Non Dimmable, 0-10V Dimmable
Driver	Integral

Performance


Maximum delivered output	714lm
Efficacy	64.9lm/W

Notes

- Recommended connections for in-ground installations with a 2-way terminal block 4-pole IP68 water stop on 24V side. Order separately.
- Painted versions are an exterior rated epoxy polyester powder coat finish for superior strength, heat and UV resistance.
- During installation and maintenance avoid scratching or damaging the finish as it may result in premature corrosion of metal surfaces. Avoid cleaning fixtures with corrosive chemicals as it may result in voiding the warranty.
- Pole IP68 water stop on 24V side. Order separately.
- Recommended connections for in-ground installations with a 2-way terminal block 4-pole IP68 water stop on 24V side. Order separately.
- LED fixtures are highly susceptible to failure due to electrical effects from poor connections, and electrical short circuits. These are frequently caused by (a) overvoltage from primary voltage sources, (b) electrostatic discharge from the exterior environment. Ensure that all outdoor fixtures are installed on GFI circuits as required by code, and use proper surge protecting devices to avoid irreversible damages to electrical components.



Dimensions



Certifications



Photometrics

For current IES files please visit arch.flosusa.com















Warranty

2 years from date of sale.

In Vitro Bollard 3

Bollard Outdoor Light Designed by Philippe Starck















Specifications

CCT	CRI	Wattage	Initial Lumens	Part Number	Finish	Power Supply
2700K	80	11W	1150lm	F018A23AU01	 01 White	Integral Not dimmable LED driver UL
				F018A23AU12	 12 Forest Green	
				F018A231AU25	 25 Terracotta	
				F018A23AU13	 13 Pale Green	
				F018A23AU30	 30 Black	
				F018A23AU18	 18 Deep Brown	
				F018A23AU33	 33 Anthracite	
3000K	80	11W	1230lm	F018A33AU01	 01 White	Integral Not dimmable LED driver UL
				F018A33AU12	 12 Forest Green	
				F018A33AU25	 25 Terracotta	
				F018A33AU13	 13 Pale Green	
				F018A33AU30	 30 Black	
				F018A33AU18	 18 Deep Brown	
				F018A33AU33	 33 Anthracite	

In Vitro Bollard 3

Bollard Outdoor Light Designed by Philippe Starck

Specifications

CCT	CRI	Wattage	Initial Lumens	Part Number	Finish	Power Supply
2700K	80	11W	1150lm	F018A23BU01	 01 White	Integral 0-10V LED driver UL
				F018A23BU12	 12 Forest Green	
				F018A23BU25	 25 Terracotta	
				F018A23BU13	 13 Pale Green	
				F018A23BU30	 30 Black	
				F018A23BU18	 18 Deep Brown	
				F018A23BU33	 33 Anthracite	
3000K	80	11W	1474lm	F018A33BU01	 01 White	Integral 0-10V LED driver UL
				F018A33BU12	 12 Forest Green	
				F018A33BU25	 25 Terracotta	
				F018A33BU13	 13 Pale Green	
				F018A33BU30	 30 Black	
				F018A33BU18	 18 Deep Brown	
				F018A33BU33	 33 Anthracite	

In Vitro Bollard 3

Bollard Outdoor Light Designed by Philippe Starck

Accessories

IN VITRO Box for ground installation housing

Part Number:
F018Z000000

