FLOS
OUTDOOR

Fixture Type .....
Job Name .....

Climber UP&Down - 87

Outdoor surface luminaire by Piero Lissoni

Description

Climber is a light designed by Piero Lissoni which, as the name suggests, climbs up the walls. Indeed, it touches them with delicacy as it does so. It is a luminaire for outdoor use for surface installation on the wall with LED light supply and with compact support for better architectural integration. Bi-emission and mono-emission versions pointing downwards.

Lamp

Lamps Type	LED
Wattage	12W
Output Nominal	2x432lm, 2x468lm, 2x504lm
Color Temperature	2700K, 3000k, 4000K
Color rendering	CRI80

Dimensions

Optical

Beam Angle	14º, 73º
Lighting Type	Wall-Washer
Light Distribution	Symmetric

Physical

Material	Aluminum
Aiming	Fixed
Weight	2.75 Pounds
Ingress Protection Rating	IP65
Finishes	Painted lacquer

01 White · 06 Grey · 05 Stainless Steel · 12 Forest Green

30 Black · 18 Deep Brown · 33 Anthracite

Installation type	Wall surface (Includes JBOX Cover Plate)
Environment	Outdoor / Wet location

Certifications

c UL us LISTED — Class 2

Photometrics

For current IES files please visit architectural.flosusa.com

Warranty

2 years from date of sale.

FLOS. USA
110 York Street
Brooklyn, NY 11201
(718).875.3472

For more information contact your representative or go to architectural.flosusa.com
©2020 Specifications and dimensions subject to change without notice. Issued 02.17.2020

c UL us LISTED

FLOS
OUTDOOR

Fixture Type .....
Job Name .....

Climber UP&Down - 87

Outdoor surface luminaire by Piero Lissoni

Electrical & Control

Voltage	110-240V
Control	Non Dimmable
Driver	Included

Performance

Maximum delivered output	825 lm
Efficacy	11.3 lm/W

Notes

Reccomended connection wit a 2 way terminal block 4 poles IP68 H2O Stop, to be ordered separately.
The aluminum versions are finished with a high-resistance coating: after a sandblasting treatment of all components to make the surface porous and ensure a greater adhesion of the paint, the external coating is appliedN with a double layer with epoxy powders according to the QUALICOAT standard.
The first layer of epoxy powder gives chemical and mechanical resistance, the second finishing layer of polyester powder ensures resistance to UV rays and atmospheric agents.
The painted surfaces are treated with alkaline and acidic washes, then rinsed with demineralized water, subjected to a chemical conversion treatment to protect against oxidation.
During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the
paint coating.
Damages on the coating exposed to outdoor conditions or water, could cause corrosion.
Chemical substances affect the anticorrosion covering protection.
For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the
insulations, which cause destructive electrical discharges
These effects are frequently caused by:
• over voltage coming from the mains' network where fixture is connected.
• electrostatic discharge (ESD) coming from the environment.
The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to
reduce the intensity of some of these phenomenon and prevent irreversible damages.
The selection of the type of
device to be used must be adjust on the electrical plant.

Dimensions

Certifications

c UL us LISTED Class 2

Photometrics

For current IES files please visit architectural.flosusa.com

Warranty

2 years from date of sale.

F L O S . U S A
110 York Street
Brooklyn, NY 11201
(718).875.3472

For more information contact your representative or go to architectural.flosusa.com
©2020 Specifications and dimensions subject to change without notice. Issued 02.17.2020

c UL us LISTED

FLOS
OUTDOOR

Fixture Type .....

Job Name .....

Climber UP&Down - 87

Outdoor surface luminaire by Piero Lissoni

How to specify

F	1	1	1	6	U	0	1
Part Number						Finish	

Part Number	Finish	CCT	Watts	Initial Lumens	Delivered Lumens	Beam Angle	CRI	Photometrics
F1116U01	White	2700	12W	2 x 432	2 x 392	14º	80	Beam Angle DIR: 14°
F1116U06	Grey							
F1116U33	Anthracite							
F1116U30	Black							
F1116U18	Deep Brown							
F1116U12	Forest Green							
F1118U01	White	3000	12W	2 x 468	2 x 425			
F1118U06	Grey							
F1118U33	Anthracite							
F1118U30	Black							
F1118U18	Deep Brown							
F1118U12	Forest Green							
F1120U01	White	4000	12W	2 x 504	2 x 458			
F1120U06	Grey							
F1120U33	Anthracite							
F1120U30	Black							
F1120U18	Deep Brown							
F1120U12	Forest Green							

h(m)	E(lx)	D(m)
1	5088	0.23
2	1272	0.47
3	565	0.70
4	318	0.93
5	204	1.17

F L O S . U S A
110 York Street
Brooklyn, NY 11201
(718).875.3472

For more information contact your representative or go to architectural.flosusa.com

©2020 Specifications and dimensions subject to change without notice. Issued 02.17.2020

C UL US LISTED

FLOS
OUTDOOR

Fixture Type .....

Job Name .....

Climber UP&Down - 87

Outdoor surface luminaire by Piero Lissoni

How to specify

Part Number	Finish	CCT	Watts	Initial Lumens	Delivered Lumens	Beam Angle	CRI	Photometrics
F1117U01	White	2700	12W	2 x 423	2 x 392	73º	80	
F1117U06	Grey							
F1117U33	Anthracite							
F1117U30	Black							
F1117U18	Deep Brown							
F1117U12	Forest Green							
F1119U01	White	3000	12W	2 x 468	2 x 425			
F1119U06	Grey							
F1119U33	Anthracite							
F1119U30	Black							
F1119U18	Deep Brown							
F1119U12	Forest Green							
F1121U01	White	4000	12W	2 x 504	2 x 458			
F1121U06	Grey							
F1121U33	Anthracite							
F1121U30	Black							
F1121U18	Deep Brown							
F1121U12	Forest Green							

Beam Angle DIR: 70°

h(m)	E(lx)	D(m)
1	315	1.42
2	79	2.85
3	35	4.27
4	20	5.70
5	13	7.12

F L O S . U S A
110 York Street
Brooklyn, NY 11201
(718).875.3472

For more information contact your representative or go to architectural.flosusa.com

©2020 Specifications and dimensions subject to change without notice. Issued 02.17.2020

C UL US LISTED