

Bellhop Bollard 380

Bollard Designed by Edward Barber & Jay Osgerby



Description


Originally conceived as a table lamp for the London Design Museum restaurant, Bellhop moves outdoors. Reminiscent of a hatted hotel porter, Edward Barber & Jay Osgerby's contemporary design offers diffused lighting which enriches landscapes and architecture.

Bellhop utilizes the latest generation LED technology installed around the lamp head, protected by an opal optic diffuser, allowing a smooth and homogeneous light to radiate all around the pole.

Lamp

Lamp Type	LED
Wattage	8W
Output Nominal	783lm, 816lm, 873lm
Color Temperature	2700K, 3000K, 4000K
Color rendering	CRI80

Dimensions



Optical

Beam Angle	85°
Lighting Type	Direct
Light Distribution	Symmetric

Physical

Material	Aluminum
Aiming	Fixed
Weight	2.65 lb
Ingress Protection Rating	IP65
Finishes	Painted lacquer

01 White

06 Grey

12 Forest Green

30 Black

18 Deep Brown

33 Anthracite

05 Stainless Steel

Installation type	Bollard ground
Environment	Outdoor / Wet Location

Certifications



Class 2

Suitable for Wet locations

Photometrics

For current IES files please visit architectural.flosusa.com

Warranty

2 years from date of sale.

Bellhop Bollard 380

Bollard Designed by Edward Barber & Jay Osgerby



Electrical & Control

Voltage	120V
Control	Non Dimmable
Driver	Integral

Performance

Maximum delivered output	607
Efficacy	75.9 lm/W

Notes


Recommended connections for in-ground installations with a 2-way terminal block 4-pole IP68 water stop on 24V side. Order separately.

Painted versions are an exterior rated epoxy polyester powder coat finish for superior strength, heat and UV resistance.

During installation and maintenance avoid scratching or damaging the finish as it may result in premature corrosion of metal surfaces. Avoid cleaning fixtures with corrosive chemicals as it may result in voiding the warranty.

LED fixtures are highly susceptible to failure due to electrical effects from poor connections, and electrical short circuits. These are frequently caused by (a) over-voltage from primary voltage sources, (b) electrostatic discharge from the exterior environment. Ensure that all outdoor fixtures are installed on GFI circuits as required by code, and use proper surge protecting devices to avoid irreversible damages to electrical components.

Dimensions



Certifications



Class 2

Suitable for Wet locations

Photometrics

For current IES files please visit
architectural.flosusa.com


Warranty

2 years from date of sale.























Bellhop Bollard 380

Bollard Designed by Edward Barber & Jay Osgerby

How to Specify



POWER LED | Non Dimmable

Part Number	Finish	CCT	Watts	Initial Lumens	Delivered Lumens	CRI	Photometrics
F003A21AU01	 White	2700	8W	783	551	80	
F003A21AU06	 Grey						
F003A21AU33	 Anthracite						
F003A21AU30	 Black						
F003A21AU18	 Deep Brown						
F003A21AU05	 Stainless Steel						
F003A21AU12	 Forest Green						
F003A31AU01	 White	3000	8W	816	580		
F003A31AU06	 Grey						
F003A31AU33	 Anthracite						
F003A31AU30	 Black						
F003A31AU18	 Deep Brown						
F003A31AU05	 Stainless Steel						
F003A31AU12	 Forest Green						
F003A41AU01	 White	4000	8W	873	607		
F003A41AU06	 Grey						
F003A41AU33	 Anthracite						
F003A41AU30	 Black						
F003A41AU18	 Deep Brown						
F003A41AU05	 Stainless Steel						
F003A41AU12	 Forest Green						

Bellhop Bollard 380

Bollard Designed by Edward Barber & Jay Osgerby

Required Accessories

Anchor Bolt Assembly

Part Number: F003Z010000

