



Caule Floor 5

Floor Outdoor Light Designed by Patricia Urquiola

Description

« Caule is an outdoor collection with simple understated lines yet strong style identity. Copying the botanical structure of a flower, the collection features a real flexible slender stem, almost a natural element, a subtle addition to any outdoor setting. »

Patricia Urquiola

Lamp

Lamp Type	LED
Wattage	10W
Output Nominal	447lm, 480lm, 513lm
Color Temperature	2700K, 3000K, 4000K
Color rendering	CRI 80

Optical

Beam Angle	52°
Lighting Type	Direct
Light Distribution	Symmetric

Physical

Material	Aluminum
Aiming	Fixed
Weight	15.9 Lbs
Ingress Protection Rating	IP66

Finishes


Painted lacquer

01 White	06 Grey	12 Forest Green	18 Deep Brown	30 Black	33 Anthracite

Installation type	Ground
Environment	Outdoor, Wet location
Impact protection	IK04



Dimensions



Certifications



Photometrics

For current IES files please visit
arch.flosusa.com

Warranty

2 years from date of sale.



Caule Floor 5

Floor Outdoor Light Designed by Patricia Urquiola

Electrical & Control

Voltage	120V
Control	Dimmer Included
Driver	Integral


Performance

Maximum delivered output	281lm
Efficacy	28.1lm/W

Notes



Dimensions



The painted versions are an exterior rated epoxy polyester powder coat finish or superior strength, heat and UV resistance.

During installation and maintenance avoid scratching or damaging the finish as it may result in premature corrosion of metal surfaces. Avoid cleaning fixtures with corrosive chemicals as it may result in voiding the warranty.

5m – 16ft cable with IP44 plug suitable for outdoor use.

Fixture should plug into covered GFI wall receptacle as required by local code.

Backlit floor dimmer switch on the IP65 cable enables ON/OFF function and brightness regulation 30–100% dimmable LED

Certifications



Photometrics

For current IES files please visit arch.flosusa.com

Warranty

2 years from date of sale.

Caule Floor 5

Floor Outdoor Light Designed by Patricia Urquiola

Specifications

CCT	CRI	Wattage	Initial Lumens	Delivered Lumens	Part Number	Finish	Power Supply
2700K	80	10W	447lm	245lm	F016M25KU01	 01 White	Integral Driver 120V
					F016M25KU12	 12 Forest Green	
					F016M25KU06	 06 Grey	
					F016M25KU30	 30 Black	
					F016M25KU18	 18 Deep Brown	
					F016M25KU33	 33 Anthracite	
3000K	80	10W	480lm	263lm	F016M35KU01	 01 White	Integral Driver 120V
					F016M35KU12	 12 Forest Green	
					F016M35KU06	 06 Grey	
					F016M35KU30	 30 Black	
					F016M35KU18	 18 Deep Brown	
					F016M35KU33	 33 Anthracite	
4000K	80	10W	513lm	281lm	F016M45KU01	 01 White	Integral Driver 120V
					F016M45KU12	 12 Forest Green	
					F016M45KU06	 06 Grey	
					F016M45KU30	 30 Black	
					F016M45KU18	 18 Deep Brown	
					F016M45KU33	 33 Anthracite	