



CE

0.7[18]

•• ••

•• ••

3.2[81]

R10



ED3307 SERIES SAE Class I LED Safety Director™

The ED3307 LED Safety Director™ is a high output directional warning with the added benefits of low amp draw, maintenance free, and long-life LED light source. Features 35 flash pattern selectable via in-cab controller. The LED Safety Arrow is the definitive traffic direction lighting solution.

Models					
PART NO.	VOLTAGE	MAX AMPS	ТҮРЕ	CABLE LENGTH	
ED3307A	12-24	2.8	Single Unit	35'	
ED3307SA	12-24	2.8	Split Arrow	35'	

Features and Benefits

- Extruded aluminum housing with polycarbonate lens
- 16 high-powered 3811 LED modules
- Temperature Range: -22°F to +122°F (-30°C to +50°C)

Flash Patterns

On	e lamp sequence then double flash
1	Flash - Wig wag
2	Right sweep - Single lamp L-R sequentially / double flash
3	Left sweep - Single Jamp R-L sequentially / double flash

3	Left sweep - Single lamp R-L sequentially / double flash
4	Center - Single lamp center out / double flash
	5

Two lamp sequence then double flash

Flash Wig wag - Alemating Right sweep - Two lamp L-R sequentially / double flash Left sweep - Two lamp R-L sequentially / double flash Center - Two lamp center out / double flash 6 8

Four lamp sequence then double flash

9	Flash - Hyper Wig wag
10	Right sweep - Six lamp L-R sequentially / double flash
11	Left sweep - Six lamp R-L sequentially / double flash
12	Center - Six lamp center out / double flash

Sequence to solid double flash

13 14

- Flash Wig wag Right sweep L-R sequentially / solid double flash Left sweep R-L sequentially / solid double flash Center Center out / solid double flash

One lamp sequence then triple flash 17 18 19 20

Flash - Hyper alternating Right sweep - Single lamp L-R sequentially / triple flash Left sweep - Single lamp R-L sequentially / triple flash Center - Single lamp center out / triple flash

Sequence on/of

15 16

22 23 24

- Flash alternating solid Flash alternating solid Right sweep L-R sequentially / double flash Left sweep R-L sequentially / double flash Center Center out / solid

Sequence (slow) on/off 25 Flash - H

4XØ0.33

22.5[572]-

ŀ

0

2.1[53]

6.1 158

5.12[130]

Flash - Hyper Wig wag
Right sweep (slow) - L-R sequentially / off
Left sweep (slow) - R-L sequentially / off
Center - Center out / solid

28.0 711

Solid arrow

26 27 28

29

30 31 32

3

Flash - Wig Wag	
Right sweep - Right side on/o	ff
Left sweep - Left side on/off	
Center - All lamps on/off	

Flash with no arrows

3	Cycle flash - Wig wag
4	Solid flash - Wig wag
5	Solid flash - Alternating

T 1800 815 000 aftermarket@eccogroup.com

www.eccoesg.com/au An ECCO SAFETY GROUP™ Brand