



Rotating LED Beacon

EB7630 Series

Features

- Unique CyclOne LED Technology with high reflectivity free-form rotating reflector
- Two rotation speeds at 120rpm and 180rpm (user selectable)
- Selectable rotation direction (clockwise, anti-clockwise)
- 30% dimmable mode for night use (user selectable, bolt base only)
- Gasket sealed tough polycarbonate lens with smooth exterior
- Gel-filled heavy duty die-cast alloy base
- Bolt base; three-hole ISO footprint and rubber mounting gasket
- Bolt base version also features bottom or side entry power cable and stainless steel fittings
- Vacuum magnetic base version supplied with 1–3 metre curly cord, cigarette and merit plug
- SAE J845 Class 1 beacon, EMC: R10, RCM, IP67

Part Numbers

EB7630A	3 Bolt Base
EB7630A-VM	Vacuum Magnetic Base
REB7630LA	Amber Replacement Lens
EB7631A	Din Pole
REB7630LA	Amber Replacement Lens

Specifications

- 10–30VDC
- Selectable rotation speed 120 or 180 RPM
- Max current draw 2.0A @ 12VDC; avg 1.3A @ 12VDC
- Bolt base height 142mm x Ø 148.5mm
- Vacuum magnetic base height 152mm x Ø 190mm



Tough polycarbonate lens

CyclOne LED Technology with free-form rotating reflector

High intensity LED

Gasket sealed lens

Die-cast alloy base

