

- NOTES:
1. ROHS COMPLIANT
 2. DIMENSIONS IN INCHES[MILLIMETERS (FOR REFERENCE)]

PROPRIETARY AND CONFIDENTIAL INFORMATION

THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN ARE THE PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS ECCO SAFETY GROUP AFFILIATES ("ECCO") AND IS ISSUED IN CONFIDENCE TO RECIPIENT FOR ENGINEERING INFORMATION PURPOSES ONLY. THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN MAY NOT BE USED, COPIED, REPRODUCED OR OTHERWISE DISCLOSED IN PART OR IN WHOLE TO THIRD PARTIES OR USED FOR ANY OTHER PURPOSE WITHOUT PRIOR ECCO WRITTEN CONSENT. ECCO RESERVES ALL PATENT, COPYRIGHT, TRADEMARK AND OTHER PROPRIETARY RIGHTS TO THIS DOCUMENT, INCLUDING ALL DESIGN, MANUFACTURING, REPRODUCTION, USE AND SALES RIGHTS THERETO. THIS DRAWING IS SUBJECT TO RECALL BY ECCO AT ANY TIME, AND YOUR POSSESSION AND/OR USE CONSTITUTES ACCEPTANCE OF THESE TERMS. ©2023 ELECTRONIC CONTROLS COMPANY



DISCLAIMER

DIMENSIONS, ILLUSTRATIONS, SPECIFICATIONS, AND CERTIFICATIONS CONTAINED IN THIS DOCUMENT ARE TYPICAL OF THE ACTUAL PRODUCT AND ARE SUBJECT TO CHANGE. ECCO ENGINEERING DOES NOT MAINTAIN FORMAL DESIGN CONTROL OF THIS PRODUCT.

SPECIFICATIONS

1. CERTIFICATIONS: **CE**; ECE R10; ; IP6K7/IP6K9K RoHS, UKCA, R148
Note: Unique components, accessories, and hardware kits are not typically included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.
2. RAW LUMENS: 1050 lumens
3. EFFECTIVE LUMENS: 970 lumens
4. ILLUMINANCE (@100 FT): 2.6 lux
5. PEAK BEAM INTENSITY: 2400 candela
6. VOLTAGE (NOMINAL): 12-24 VDC
7. VOLTAGE (EXTREME): 9-32 VDC
8. CURRENT (PEAK): 1.2A (@ 12 VDC NOMINAL)
9. POWER (MAXIMUM): 15.9W (@ 12 VDC NOMINAL)
10. TEMPERATURE RANGE: -40°F (-40°C) TO 149°F (65°C)
11. CONNECTION: 2 CONDUCTOR CABLE
12. MOUNTING: SINGLE BOLT
13. HOUSING MATERIAL: ALUMINUM
14. LENS MATERIAL: POLYCARBONATE
15. PRODUCT WEIGHT: 1.2 LBS (0.54 Kg)

REVISION HISTORY		
REV.	DESCRIPTION	DATE
02	REVISED PER EB0008	2023-03-30
A	INITIAL RELEASE PER EB0008	2023-04-04
B	REVISED PER EB0008	2023-05-30

SCALE 1:2	APPROVALS	DATE	 ECCO ® www.eccolink.com Americas (800) 635-5900 Europe +44 (0)113 237 5340 Asia Pacific +61 (0)3 63322444	
CAD GENERATED DRAWING DO NOT MANUALLY UPDATE.	DRAWN BY NT	2023-05-25		
	CHECKED BTK	2023-05-30		
	MECH. ENG.			
TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:	ELEC. ENG.		WORK LAMP, 9 LED, SQUARE, FLOOD, 12-24V	
MILLIMETERS DECIMALS XX. ± 1.0mm XX.X ± 0.5mm	TEST ENG.		CUSTOMER PART NO. E92006W	
INCHES DECIMALS X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	SALES.		SIZE: A	DWG. NO. E92006W
ANGLES ± 0.5° FRACTIONS ± 1/64	Electronically Controlled Use Latest Copy		SHEET 1 OF 1	Project: EB0008
THIRD ANGLE PROJECTION 		Date Created: 2023-03-22	REV. B	