

P65 GRAVITY FEED PAVER




GRAVITY FEED HOPPER.

The gravity fed 6-ton (5.4 mt) hopper features an hydraulically raised floor and wings with two independently operated hydraulic cut-off doors for exceptional material management.




ELECTRIC SCREED HEAT.

The Weiler designed screed delivers outstanding mat quality and a standard paving range of 7' 8" (2.3 m) to 13' (3.35 m). Four heating elements and optional heated end gates are powered by an hydraulically driven 12 kW generator.



POWERTRAIN.

A Cat® C2.2 Tier 4 engine provides 49 hp (36 kW) and powers a 2-speed hydrostatic drive with 180 fpm (55 m/min) max paving speed and 300 fpm (91 m/min) max transport speed.



SIMPLE OPERATION.

Dual side operation with manual ground drive controls, independent augers with reverse and color LCD display providing machine conditions and diagnostics.



DURABLE UNDERCARRIAGE.

The undercarriage features 55" (1397 mm) track length with 39" (990 mm) of ground contact, 12" (305 mm) steel track pads, a sprocket driven 125 mm track chain pitch and automatic track tensioning.



FAST SERVICE.

Remote grease lines, spray down system with 7 gal (26 L) tank and coiled hoses, large engine access door and Caterpillar dealer service and support keep your machine up and running with limited down time.

P65 SPECIFICATIONS

WEIGHT	12,600 lb	5715 kg	SCREED WEIGHT	2,100 lb	952 kg	ENGINE	Cat® C2.2 Tier 4	
LENGTH	9' 9"	2.97 m	MAIN PLATE WIDTH	13"	330 mm	PAVING SPEED	180 fpm	55 mpm
WIDTH	98"	2.48 m	EXTENSION PLATE WIDTH	7"	178 mm	TRANSPORT SPEED	300 fpm	91 mpm
HEIGHT	70"	1.78 m	SCREED HEAT	Electric - 4 elements		FUEL CAPACITY	25 gal	94 L
TRUCK CLEARANCE	20.75"	557 mm	VIBRATION	1 x 2500 vpm		HYDRAULIC CAPACITY	22 gal	83 L
AUGER DIAMETER	9"	229 mm	MAX AUGER SPEED	125 rpm		SPRAY DOWN CAPACITY	7 gal	26 L

POWERTRAIN

- Cat® C2.2 Tier 4 engine provides 49 hp (36 kW)
- 2-speed hydrostatic drive, 300 fpm (91 m/min) transport speed
- Automatic track tensioning
- 55" (1397 mm) track length with 39" (990 mm) of ground contact
- 12" (305 mm) steel track pads
- Sprocket driven 125 mm track chain pitch
- Hydraulically driven 12 kW generator

MATERIAL DELIVERY

- Gravity fed, hydraulically raised hopper floor and wings
- 6-ton (5.4 mt) hopper
- 2 independently operated hydraulic cut-off doors

SIMPLE OPERATION

- Dual side operation
- Manual ground drive controls
- Color LCD display provides conditions and diagnostics
- Pause mode enables return to same settings

SALES AND SERVICE

Sold and serviced exclusively through Caterpillar dealers worldwide.

WWW.WEILERPRODUCTS.COM

SCREED

- 7' 8" (2.3 m) to 13' (3.35 m) standard paving width
- 4 element electric heated screed
- Two independently operated hydraulic 9" (228 mm) augers w/reverse
- Optional sonic feed sensors

SERVICE/MAINTENANCE

- 7 gal (26 L) spray down system with 2 hoses/nozzles
- Braided electrical harnesses and sealed connections
- 12-volt electric system with automotive-type fuses
- Remote hydraulic diagnostic ports
- Remote grease fittings
- Large engine access door

OPTIONAL EQUIPMENT

- LED strobe light
- Work lights
- Heated end gates
- Sonic controlled augers
- Spray down tank
- Screed mounted cutoff shoes

WARRANTY

12 months standard. Extended warranty available.