



FLASH TEST REPORT

12/07/2023 13:57:58

Execution

State of charge Date Executed by Vehicle

Brand Model VIN Mileage

17 %

Carla AB

Mercedes-Benz EQA - 66,5 kWh W1N2437011J003497 5,757 km

Analysis Result

AVILOO SCORE



High voltage battery usage and history Analysis of charging & driving behavior	50 / 50
High voltage battery performance Analysis of cell voltages and module temperatures.	30 / 30
High voltage battery control unit Check of signals and calculations of the battery management control unit.	10 / 10
Electrical low voltage system Check of 12 V battery state and power supply.	5 / 5
Vehicle communication interface Check of communication via the diagnostic interface.	5 / 5

DI Wolfgang Berger MBA Managing/director

DI Nikolaus Mayerhofer Managing director Dr. Marcus Berger COO/CFO and Partner





EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

13:57:55 AVILOO Box connected.
13:57:58 Flash Test started.
13:58:02 Vehicle detected.
13:58:06 Starting data acquisition.
14:00:06 Finished data acquisition.
14:00:20 Analyzing data.

14:00:20 Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

 VIN
 W1N2437011J003497

 Date
 12/07/2023 13:57:58

 Mileage
 5,757 km

Measurements High Voltage System

• • •	
Battery temperature	21 °C
Maximum cell temperature deviation	1 °C
Pack voltage	350.6 V
Maximum cell voltage deviation	18.07 mV
Peak current during check	-8.28 A
State of Health (SoH - read from car manufacturer)*	102.03 %

Measurements Low Voltage System

Power supply 12V system 14.87 V

*The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.



Brown Boveri Strasse 16 2351 Wiener Neudorf Austria Tel: +43 2236 374 036 Mail: info@aviloo.com Web: www.aviloo.com

UID Nr.: ATU 737 81605 FN: 502117 h

