

FLASH TEST REPORT

Execution

State of charge **100 %**
Date 25/04/2023 08:49:46
Executed by Carla AB

Vehicle

Brand Kia
Model Niro EV 64,8 kWh
VIN KNACR811FP5008648
Mileage 6,648 km

Analysis Result

AVILOO SCORE

99

/ 100

High voltage battery usage and history

Analysis of charging & driving behavior

50 / 50

High voltage battery performance

Analysis of cell voltages and module temperatures.

30 / 30

High voltage battery control unit

Check of signals and calculations of the battery management control unit.

10 / 10

Electrical low voltage system

Check of 12 V battery state and power supply.


4 / 5


Vehicle communication interface

Check of communication via the diagnostic interface.

5 / 5


DI Wolfgang Berger MBA
Managing director


DI Nikolaus Mayerhofer
Managing director


Dr. Marcus Berger
COO/CFO and Partner



EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

08:49:43 AVILOO Box connected.
08:49:46 Flash Test started.
08:49:49 Vehicle detected.
08:49:54 Starting data acquisition.
08:51:54 Finished data acquisition.
08:52:07 Analyzing data.
08:52:08 Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

VIN	KNACR811FP5008648
Date	25/04/2023 08:49:46
Mileage	6,648 km

Measurements High Voltage System

Battery temperature	19 °C
Maximum cell temperature deviation	1 °C
Maximum cell voltage deviation	20 mV

Measurements Low Voltage System

Power supply 12V system	13.84 V
12V battery voltage	11.81 V

*The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.

