AVILOO
BATTERY DIAGNOSTICS

FLASH TEST REPORT

Execution

State of charge	82 %
Date	20/03/2023 15:17:08
Executed by	Carla AB

Vehicle

Brand	Nissan
Model	Leaf ZE1
VIN	SJNFAAZE1U0000155
Mileage	83,987 km

Analysis Result

AVILOO SCORE 93 / 100

High voltage battery usage and history Analysis of charging & driving behavior	43 / 50
High voltage battery performance Analysis of cell voltages and module temperatures.	30 / 30
High voltage battery control unit Check of signals and calculations of the battery management control unit.	10 / 10
Electrical low voltage system Check of 12 V battery state and power supply.	5 / 5
Vehicle communication interface Check of communication via the diagnostic interface.	5 / 5

DI Wolfgang Berger MBA
Managing director

DI Nikolaus Mayerhofer
Managing director

Dr. Marcus Berger
COO/CFO and Partner

EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

15:17:05	AVILOO Box connected.
15:17:08	Flash Test started.
15:17:20	Vehicle detected.
15:17:25	Starting data acquisition.
15:19:26	Finished data acquisition.
15:19:38	Analyzing data.
15:19:40	Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

VIN	SJNFAAZE1U0000155
Date	20/03/2023 15:17:08
Mileage	83,987 km

Measurements High Voltage System

Battery temperature	9 °C
Maximum cell temperature deviation	3 °C
Pack voltage	383.39 V
Maximum cell voltage deviation	10.01 mV
Peak current during check	-4.61 A
State of Health (SoH - read from car manufacturer)*	91.94 %

Measurements Low Voltage System

12V battery voltage	11.92 V
Power supply 12V system	14.39 V

*The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.

AVILOO BATTERY DIAGNOSTICS

AVILOO GmbH
Brown Boveri Strasse 16
2351 Wiener Neudorf
Austria

Tel: +43 2236 374 036
Mail: info@aviloo.com
Web: www.aviloo.com

UID Nr.: ATU 737 81605
FN: 502117 h