



# FLASH TEST REPORT

## Execution

State of charge 18 %  
Date 28/07/2023 08:47:42  
Executed by Carla AB

## Vehicle

Brand Skoda  
Model Enyaq iV - 77 kWh  
VIN TMBLE7NY9NF032486  
Mileage 29,019 km

## Analysis Result

# AVILOO SCORE

97  
/ 100

### High voltage battery usage and history

Analysis of charging & driving behavior

48 / 50

### High voltage battery performance

Analysis of cell voltages and module temperatures.

29 / 30

### High voltage battery control unit

Check of signals and calculations of the battery management control unit.

10 / 10

### Electrical low voltage system


Check of 12 V battery state and power supply.


5 / 5


### Vehicle communication interface

Check of communication via the diagnostic interface.

5 / 5

  
DI Wolfgang Berger MBA  
Managing director

  
DI Nikolaus Mayerhofer  
Managing director

  
Dr. Marcus Berger  
COO/CFO and Partner



# EXPLANATION OF THE BATTERY FLASH TEST

## ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

## FLASH TEST EXECUTION PROTOCOL

08:47:39 AVILOO Box connected.  
08:47:42 Flash Test started.  
08:47:46 Vehicle detected.  
08:47:50 Starting data acquisition.  
08:49:50 Finished data acquisition.  
08:49:59 Analyzing data.  
08:50:00 Analysis completed.

## DETAILED RESULTS OF PERFORMED CHECKS

### Vehicle Information

VIN	TMBLE7NY9NF032486
Date	28/07/2023 08:47:42
Mileage	29,019 km

### Measurements High Voltage System

Battery temperature	21 °C
Maximum cell temperature deviation	0.5 °C
Pack voltage	342.71 V
Maximum cell voltage deviation	5.12 mV
Peak current during check	-5.51 A
State of Health (SoH - read from car manufacturer)*	96.17 %

### Measurements Low Voltage System

Power supply 12V system	14.48 V
-------------------------	---------

\*The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.

