



FLASH TEST REPORT

Execution

State of charge Date Executed by 41.92 % 14/07/2023 09:02:27 Carla AB

Vehicle

Brand Model VIN Mileage

Tesla Model X 5YJXCCE2XJF129349 68,590 km

Analysis Result

AVILOO SCORE



| High voltage battery usage and history Analysis of charging & driving behavior | 45 / 50 |
|---|----------------|
| High voltage battery performance Analysis of cell voltages and module temperatures. | 27 / 30 |
| High voltage battery control unit Check of signals and calculations of the battery management control unit. | 10 / 10 |
| Electrical low voltage system Check of 12 V battery state and power supply. | 5 / 5 |
| Vehicle communication interface Check of communication via the diagnostic interface. | 5 / 5 |

DI Wolfgang Berger MBA Managing director



DI Nikolaus Mayerhofer Managing director

loc.

Dr. Marcus Berger COO/CFO and Partner





EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

| 09:02:24 | AVILOO Box connected. | |
|----------|----------------------------|--|
| 09:02:27 | Flash Test started. | |
| 09:05:08 | Starting data acquisition. | |
| 09:05:08 | Vehicle detected. | |
| 09:05:38 | Finished data acquisition. | |
| 09:05:45 | Analyzing data. | |
| 09:05:47 | Analysis completed. | |

DETAILED RESULTS OF PERFORMED CHECKS

| Vehicle Information | |
|------------------------------------|---------------------|
| VIN | 5YJXCCE2XJF129349 |
| Date | 14/07/2023 09:02:27 |
| Mileage | 68,590 km |
| Measurements High Voltage System | |
| Battery temperature | 19.07 °C |
| Maximum cell temperature deviation | 0.49 °C |
| Pack voltage | 308.85 V |
| Maximum cell voltage deviation | 19.2 mV |
| Peak current during check | -3.93 A |
| Measurements Low Voltage System | |
| Power supply 12V system | 13.33 V |



AVILOO GmbH

Brown Boveri Strasse 16 2351 Wiener Neudorf Austria

Tel: +43 2236 374 036 Mail: info@aviloo.com Web: www.aviloo.com

UID Nr.: ATU 737 81605 FN: 502117 h

