



FLASH TEST REPORT

03/08/2023 12:55:01

Execution

State of charge Date Executed by

Vehicle

Brand Model VIN Mileage

61 %

Carla AB

Mercedes-Benz EQC 400 - 85 kWh W1K2938901F042681 28,691 km

Analysis Result

AVILOO SCORE



High voltage battery usage and history Analysis of charging & driving behavior	50 / 50
High voltage battery performance Analysis of cell voltages and module temperatures.	30 / 30
High voltage battery control unit Check of signals and calculations of the battery management control unit.	10 / 10
Electrical low voltage system Check of 12 V battery state and power supply.	5 / 5
Vehicle communication interface Check of communication via the diagnostic interface.	5 / 5

DI Wolfgang Berger MBA Managing/director

DI Nikolaus Mayerhofer Managing director

Dr. Marcus Berger COO/CFO and Partner





EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

12:54:58 AVILOO Box connected.12:55:01 Flash Test started.

12:55:04 Vehicle detected.12:55:09 Starting data acquisition.

12:57:09 Finished data acquisition.

12:57:22 Analyzing data.

12:57:22 Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

 VIN
 W1K2938901F042681

 Date
 03/08/2023 12:55:01

 Mileage
 28,691 km

Measurements High Voltage System

Battery temperature 20 °C

Maximum cell temperature deviation 0 °C

Pack voltage 368.01 V

Maximum cell voltage deviation 6.05 mV

Peak current during check -13.4 A

State of Health (SoH - read from car manufacturer)*

Measurements Low Voltage System

Power supply 12V system 14.81 V

*The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.



Tel: +43 2236 374 036 Mail: info@aviloo.com Web: www.aviloo.com

UID Nr.: ATU 737 81605 FN: 502117 h

