



FLASH TEST REPORT

07/07/2023 07:47:21

_		 •
Exe	\sim 1	 -
-x		

State of charge Date Executed by **Vehicle**

Brand Model VIN Mileage

17.29 %

Carla AB

Tesla Model X 5YJXCCE29KF188958 94,279 km

Analysis Result

AVILOO SCORE

94

High voltage battery usage and history Analysis of charging & driving behavior	46 / 50
High voltage battery performance Analysis of cell voltages and module temperatures.	28 / 30
High voltage battery control unit Check of signals and calculations of the battery management control unit.	10 / 10
Electrical low voltage system Check of 12 V battery state and power supply.	5 / 5
Vehicle communication interface Check of communication via the diagnostic interface.	5 / 5

DI Wolfgang Berger MBA Managing/director

DI Nikolaus Mayerhofer Managing director

Dr. Marcus Berger COO/CFO and Partner





EXPLANATION OF THE BATTERY FLASH TEST

ANALYSIS METHOD

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

FLASH TEST EXECUTION PROTOCOL

07:47:18 AVILOO Box connected.07:47:21 Flash Test started.

07:49:55 Starting data acquisition.

07:49:55 Vehicle detected.

07:50:25 Finished data acquisition.

07:50:33 Analyzing data.07:50:35 Analysis completed.

DETAILED RESULTS OF PERFORMED CHECKS

Vehicle Information

VIN	5YJXCCE29KF188958
Date	07/07/2023 07:47:21
Mileage	94,279 km
Measurements High Voltage System	
Battery temperature	23.26 °C
Maximum cell temperature deviation	1.33 °C
Pack voltage	334.72 V
Maximum cell voltage deviation	5.54 mV
Peak current during check	-6.12 A

Measurements Low Voltage System

Power supply 12V system 13.23 V

*The SoH shown here was not calculated by AVILOO but corresponds to the SoH read out from the battery management system and calculated by the manufacturer. AVILOO therefore does not guarantee the correctness of this SoH.



UID Nr.: ATU 737 81605 FN: 502117 h

