



## **FLASH TEST REPORT**

~	•.	^	
Ju		v	
	cu	cuti	cutio

State of charge Date Executed by **Vehicle** 

96.39 % 12/07/2023 08:51:41 Carla AB Brand Model VIN Mileage Tesla Model X 5YJXCCE27MF312597 41,634 km

### **Analysis Result**

# **AVILOO SCORE**



High voltage battery usage and history Analysis of charging & driving behavior	<b>47</b> / 50
High voltage battery performance Analysis of cell voltages and module temperatures.	<b>29</b> / 30
High voltage battery control unit Check of signals and calculations of the battery management control unit.	10 / 10
Electrical low voltage system Check of 12 V battery state and power supply.	<b>5</b> / 5
Vehicle communication interface Check of communication via the diagnostic interface.	<b>5</b> / 5

DI Wolfgang Berger MBA Managing/director

DI Nikolaus Mayerhofer Managing director Dr. Marcus Berger COO/CFO and Partner





## EXPLANATION OF THE BATTERY FLASH TEST

#### **ANALYSIS METHOD**

The analysis performed is a combined result of: The communication quality between the diagnostic hardware AVILOO Box and the on-board diagnostic interface of the vehicle. The live battery data and data that indicates the previous use of the high voltage battery, which is made available to the AVILOO Box by the battery management system during the measurement. The plausibility check and classification of the battery condition using the collected values and a comparison with the AVILOO Battery Cloud using Big Data algorithms.

#### FLASH TEST EXECUTION PROTOCOL

08:51:38 AVILOO Box connected.

08:51:41 Flash Test started.

08:55:07 Starting data acquisition.

08:55:07 Vehicle detected.

08:55:37 Finished data acquisition.

08:55:46 Analyzing data.

08:55:48 Analysis completed.

#### **DETAILED RESULTS OF PERFORMED CHECKS**

#### **Vehicle Information**

VIN 5YJXCCE27MF312597
Date 12/07/2023 08:51:41
Mileage 41,634 km

#### Measurements High Voltage System

Battery temperature 25.21 °C
Maximum cell temperature deviation 2.04 °C
Pack voltage 397.45 V
Maximum cell voltage deviation 3.96 mV
Peak current during check -4.91 A

#### Measurements Low Voltage System

Power supply 12V system 13.23 V



Brown Boveri Strasse 16 2351 Wiener Neudorf Austria Tel: +43 2236 374 036 Mail: info@aviloo.com Web: www.aviloo.com

UID Nr.: ATU 737 81605 FN: 502117 h

