

Utyl

SUT0001

Single shelter



Technical description

Shelter made of electrogalvanized steel, polyester powder-coated. Roofing in cellular polycarbonate, gutter in electrogalvanized steel.

Seawater atmosphere protection available upon request.

Dimensions: 2.51 × 2 m • H 2.46 m

Capacity: 6 bikes

Weight: 167.4 kg

Lifespan

The estimated lifespan of the product exceeds 25 years.

Maintenance and lifespan

It is recommended to regularly clean metal surfaces with soapy water. Make sure to use non-aggressive products. Never use corrosive products or scouring pads. Once a year, check that there are no signs of oxidation on the metal parts.

Installation

Mandatory floor fixation on base plate. Chemical sealing.

Fixing with Anchor rods M14 × 300, supplied only on request.

Fixation hole: 16 × 28 mm







Cutzomization

Customization available upon request.

Finish

The finish shown is in Black 2100 sanded metal, code +.M05.

Finish options available in any of the standard shades from the AUBRILAM color chart. Other colors available upon request.

Metal			
			
Graphite code+.M01	Silver code+.M02	RAL 7006 MFT code+.M03	Grey 2900 sanded code+.M04
			
Black 2100 sanded code+.M05	Black 2200 sanded code+.M06		

