

SES-E-V

Product description:

SES-E-V is a galvanised push-fit steel end cap made of rolled mild steel with zinc-nickel alloy plating.

This push-fit end cap is used for Staro Steck-ES-V steel conduits. An advantage is that edge protection is provided.



VDE 0605
DIN EN 61386-21

Special features

This product is suited for the installation of circuit integrity cables (E30/ E60/ E90) and has been tested in the system.

Cat. No.:	Type	Outside Ø mm	Content	PU	Weight PU/kg	Overall length mm
20590016	16	23,3	25	STK	0,750	55,0
20590020	20	28,2	50	STK	1,750	55,0
20590025	25	35,3	50	STK	3,100	60,0
20590032	32	44,0	50	STK	4,700	70,0
20590040	40	54,0	25	STK	3,300	80,0
20590050	50	66,5	10	STK	1,940	95,0
20590063	63	82,5	5	STK	1,395	110,0

All dimensions without tolerances are for information only.

Material properties

Zero halogen	DIN VDE V 0604-2-100	
Low smoke	DIN EN 61034-2	
Non-flame propagating	DIN EN 61386-1	●
UV-resistant	DIN 53387	
Highspeed		

Fields of application

on plaster	●	machines	●
under plaster	●	hot asphalt	●
on wood	●	under screed	●
underground installation	●	prefabricated construction	●
in concrete	●	outdoor	●

Chemical properties

Resistant to	oils, paint, water, weak alkalis and solvents
Limitedly resistant to	acids and strong bases
Not resistant to	sulphur



SES-E-V

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

**Information can be obtained from our technical consultants at
+49 9525 88-8123**