



Product data sheet

49617 - Distributor housing for fuse protection (accessory from 49615)



Accessories for junction box 49615 Application : Fuse protection of feeder or sub-distribution up to 76A. Break-out on the output side for cable glands M25, M32, M50 (cable gland output side not included).

Application:

Fuse protection of cross-section reductions

-Branch circuit protection up to 63 A

Flat cable feeder protection up to 63 A

Cable gland (not included): M25, M32 (break-out), M50 (break-out)

Number of modules: 5HP (17.5mm)

On request, the enclosures can be equipped with FI or FI/LS.

Characteristics

Base Unit

Piece

availability

Delivery according to agreement

group

170000

Packaging unit

1

country of origin

CH

Customs tariff number

8536.9080

Weight (g)

526 g

Color

gray

Technical data

Fire load (KWh)

4,05 kWh

Dimensions length x width x height (mm)

200x116x105 mm



Product data sheet

49617 - Distributor housing for fuse protection (accessory from 49615)

Degree of protection	IP65
Material	Polycarbonate
Rated current heavy current part (A)	76(16mm ²) A
Halogen free	Yes
Operating Temperature (°C)	-15 to 85 °C
Plastic parts	Halogen-free



Product data sheet

49617 - Distributor housing for fuse protection (accessory from 49615)

Product accessories



Product data sheet

49617 - Distributor housing for fuse protection (accessory from 49615)

Product systems



Flat cable system Power 5G16 mm² (IP65)

Robust, weatherproof and powerful - a flexible power supply solution for construction temporary buildings, offices, tunnels, ships, halls, trade fairs and e-mobility.



Flat cable system Power 5G16 mm² (IP65)



Flat cable system Power 5G16 mm² (IP65)



Flat cable system Power 5G25 mm² (IP65)

Ideal for construction temporary buildings, offices, tunnels, halls, trade fairs and e-mobility. Robust, weatherproof and powerful - perfect for temporary or permanent power supply.



Flat cable system Power 5G25 mm² (IP65)



Flat cable system Power 5G25 mm² (IP65)

