






DATASHEET

RJ45 Keystone UTP, Cat.6, 250MHz, component certified, white



General data

Specifications:

Plastic housing PC+ABS
 Compact cable presorter for AWG 24/1 .. 22/1
 Pair management according to TIA 568A /B colour codes
 Appropriate for distribution panels and frames with keystone slots

Scope of delivery:

1 x RJ45 keystone, Cable coder, 1 x hinged dust cover, 1 x cable tie, 1 x mounting instruction

Allgemeine Daten

Type of connector	RJ45 8(8)
Model	jack
Suitable for litz wire conductor	True
Suitable for solid core	True
AWG-range	24 - 22
Suitable for flat cable	False
Max. cable diameter	8.5 mm

This datasheet was created automatically on 30-09-2024 . Technical changes reserved.



DATASHEET

RJ45 Keystone UTP, Cat.6, 250MHz, component certified, white

Suitable for round cable	True
--------------------------	------

General data

Housing material	Plastic
Connection type	Insulation displacement connector
Special tool necessary	False
Category	6
For UAE suitable	True
Complaint to UL94	V-0

Mechanical characteristics

Mating cycles	≥ 750
Dust cover	true
Contact coating	50 μ"

Environmental conditions

Temperature range	-40 - 66 °C
-------------------	-------------

Electrical characteristics

Insulation Resistance	≥ 500 MΩ
Current Rating	2 A
Contact Resistance	≤ 20 mΩ
Dielectric Withstanding Voltage	1000 V AC 60Hz
4PPOE certified	True

Structure du câble

screened	False
----------	-------

Available variants

ArtNr.	Bezeichnung	Colour
E-20080	RJ45 Keystone UTP, Cat.6, 250MHz, component certified, white	white
E-20081	RJ45 Keystone UTP, Cat.6, component certified, black	black


Drawings

This datasheet was created automatically on 30-09-2024 . Technical changes reserved.



DATASHEET

RJ45 Keystone UTP, Cat.6, 250MHz, component certified, white



This datasheet was created automatically on 30-09-2024 . Technical changes reserved.

