Euro H1 GS1 Pallet: The range

7842.001



Ext. (mm) 1200 x 800 x 166 Weight (Kg) 18

Stacked height (mm) 159
Static load (Kg) 5000
Dynamic load (Kg) 1250
Racking load (Kg) 850

3 runners, 7mm safety rim and location

7842.002



Ext. (mm) 1200 x 1000 x 166

Weight (Kg) 23.9
Stacked height (mm) 159
Static load (Kg) 5000
Dynamic load (Kg) 1250
Racking load (Kg) 850
3 runners and 7mm safety rim

7843.003



(xt. (mm) 1200 x 800 x 160 (Veight (Kg) 18

Weight (Kg)18Stacked height (mm)160Static load (Kg)5000Dynamic load (Kg)1250Racking load (Kg)850

3 runners without safety rim



Euro H1 GS1 Pallet

3600

Schoeller Allibert

Returnable Plastic

Packaging Solutions

Detailed features



Centring blocks:

This version of top deck holds E boxes in place, allow robotized pallet filling and promotes airflow between crates.



7 mm rim on 4 sides on the top deck:

Prevent the load from slipping and ensure stability of empty stacked pallets on return trips.



Smooth closed runners:

3 runners to ensure racking capacity. Works seamlessly on conveyors. Compatible with tipping forklift trucks. Easy to clean. No dirt retention.





Schoeller Allibert

Innovating your logistics for a better world





Please visit our website www.schoellerallibert.com

Euro H1: meets the logistics needs of all fresh products

Hygienic, Standard and Safe



Secure loads

7 mm rim prevents loads and boxes from slipping. Centring blocks on the GS1 certified version enable "E"series meat boxes and Euronorm containers to be both separated and firmly held in place, and allows full layers of boxes to be palletised at the same time

Edges also insure stability of empty pallets when stacked.

Outstanding performance

With only an 18 kg tare weight, the Euro H1 can take up to 5000 kg static load, and 1250 kg dynamic load, meeting the toughest demands of food and non-food industries.

Hygienic

The meat and food supply chain standard pallet.

Ventilated-smooth welded runners – easy to clean.

Food contact certified.

Made in deep-freeze resistant virgin HDPE.

Fast cooling process

The deck's ventilated design, combined with the centring block which separates containers, promotes air flow to speed cooling.

Safe automated handling and racking

The 3 closed runners are chamfered on both sides for safe, long term forklift truck handling. They work seamlessly with most automated handling systems and speed up conveying.

The H1 pallet is rackable and can take up to 850kg unit load on high bay racks.

Euro H1 GS1

The standard for meat and food supply chains. Available in 3 different versions.

Standard and Certified

Tested according to DIN EN ISO 8611-1 and GS1 certified, meeting the toughest international standards.

Compatible with existing H1 pallet fleets on the market.

Customization and tracking

Secure your pallet fleet, increase management efficiency and enhance brand awareness.

Recessed zones for self-adhesive labels on feet.

Inserts for your logo and message on feet.

RFID tags and Barcode label ready for 100% reliable tracking.