360° Schoeller Allibert

Returnable Plastic Packaging Solutions

Intermediate Bulk Containers On**Flow**®

Excelsior®



Schoeller Allibert Innovating your logistics for a better world Schoelle

er Alfibert

Excelsion



Table of contents

Our 360° approach

Design and engineering









Combo Fructus[®]



The new "44x48" foldable IBC for tomato and fruit juice.

1. Outstanding performance: The Combo Fructus[®] is strong and durable: its double wall structure enables a 1500 kg unit load and a stack load of 8000 kg (4on1).

Maximum safety when stacked full thanks to the T shaped locking system between sides and ends. With up to 73% folding ratio Combo Fructus[®] optimizes reverse logistics costs and enhances fast return on investment.

- 2. The most Hygienic foldable plastic IBC: 100% smooth and double wall sturdy design increases internal volume and ensure compatibility with high speed filling processes.
- 3. Improved handling and labor saving. Easily erected and folded by a single operator : unique side walls locking system while erecting enables one operator to handle the Combo Fructus®.



More details see product **page 06**

Combo Excelsior®



The Combo Excelsior® is the new standard Foldable IBC for international logistics of the food processing, cosmetics and pharmaceutical industries

- 1. The best logistics solution for maximised profitability: The Combo Excelsior standard footprint, 1200X1000, its 1000 L capacity and 3100kg dynamic load ensure optimized payload in road and railroad transportation. With the best folding ratio on the market.
- 2. The best folding ratio on the market reduciing reverse logistics cost and lowerign environmental impact
- 3. Outstanding performance: The combo Excelsior® is strong and durable: its double wall structure enables a 1500kg unit load and a stack load of 8000kg (4on1).
- 4. The most Hygienic foldable plastic IBC: 100% smooth and double wall sturdy design increases internal volume and ensure compatibility with high speed filling processes.

More details see product p:ge O6

Intermediate Bulk Containers | OnFlow®

ComboLife[®] foldable IBC: for food, pharmaceutical and non hazardous chemical and non chemical products handling and transport, our Foldable IBC provides 100% hygiene and safety. Thanks to its unique folding ratio, our IBC offers maximum cost savings on return trips. Tankgo[®], the UN certified IBC for all types of hazardous liquids, up to 1.9 density, 100% plastic, it needs no maintenance and is fully recyclable.

ComboLife[®] 65 / ComboLife[®] 285



- 1. Lightweight and standard footprint, ComboLife 65 combines a practical, cost-effective distribution system with great resource efficiency.
- 2. The ComboLife 65 and 285 are compact foldable IBC's designed to handle a variety of fluid products. It comes with a level indicator and optional features include a drain hole in the base and a lid with a tamper-evident locking device.
- 3. The ComboLife 285 can easily be handled by one operator offering a 1000L usable volume.
- 4. Designed to handle 1000 litres, it has space-efficient dimensions that provide optimal stacking and cubing during transport. A drop-down door is an optional feature that facilitates easy liner installation or the loading of bulky goods.

More details see product page 07



TankGo®



- 1. The UN certified IBC range for hazardous liquids
- 2. One square foot print 1160 x 1160 and three heights for 500, 800 and 1000 litres of hazardous chemicals logistics and storage.
- 3. TankGo® is fully certified according to UN ADR, RID IMDG , for dangerous and corrosive liquids and fluids up to 1.9 density.
- 4. 100% plastic TankGo[®] range does not need any maintenance unlike the metal grid models with liner and wooden pallet.
- 5. The TankGo® IBC's can be equipped with a wide variety of fittings, valves and discharge devices according to the content and end use. All models are fully recyclable at the end of their long service life.
- 6. Designed and manufactured for intensive reuse, TankGo® IBC's are rotationally molded, thick walled and withstand harsh industrial conditions.
- 7. For liquid food non dangerous goods, SAFI ball valve DN50 can be supplied in food approved material.



More details see product page 08

Combo Fructus®: the new 44"x48" foldable IBC for tomato paste and fruit juice Safe, hygienic, profitable and sustainable

Combo Excelsior[®]: the New standard Foldable IBC for International Logistics Safe, hygienic and efficient for food processing, cosmetics and pharmaceutical industries

The most hygienic foldable IBC

- •100% smooth, easy to clean design from base to lid. No dirt or water traps, bugs and needle contamination proof.
- •100% smooth and double wall sturdy design increases internal volume and ensures compatibility with high speed filling processes.



Improved handling and labor saving

- Easily erected and folded by one operator only: unique side walls locking while erecting enable one operator to handle the Combo Fructus[®].
- •Non sequential folding thanks to floating hinges saving time and labor. Ergonomic handles on sides.

The best logistics solution

- optimised payload in road and railroad transportation.
- The best folding ratio on the market: with only 341 mm incremental folded height, 7 folded Combo fit in a standard truck reducing reverse logistics cost and lowering environmental impact.



Outstanding performance

•The Combo Fructus® is strong and durable: its double wall structure enables a 1500 kg unit load and a stack load of 8000 kg (4on1). Maximum safety when stacked full thanks to the T shaped locking system between sides and ends, and the double wall water-tight lid allowing strapping.

Maximised profitability

•Up to 73% folding ratio for the CF 315, one of the best folding ratio on the market. **7 folded Combos** piled in a standard truck for reduced logistics costs and lower environmental impact/gas emission.





Improved handling and labor saving

- Easily erected and folded by one operator only: handlind and filling efficiency. Non sequential folding saves time and labour.
- Improved ergonomics and set up: the large easy to open and self locking drop door on front combines easy operator access zone while maintaining the panel strength thanks to it's V shape. Improved bottom discharge zone speeds up the liner and valve set up and removal.

•The Combo Excelsior® 1200 x 1000 standard footprint, 1000 L capacity and 3200kg dynamic load ensure

The most hygienic and safe foldable IBC

- •100% smooth and double wall sturdy design increases internal volume and ensures **compatibility** with high speed filling processes.
- Fork tine guides on base, strong three skids base and anti-slip plugs reinforce safety and speed handling.

Combo Fructus[®] top benefits

- 1. A real safe for tomato paste and fruit juice: water tight, dust tight, needle and bug proof for maximum safety. All surfaces smooth inside and outside from base to lid.
- 2. Optimized mechanical performance with 1500 kg unit load and 3200 kg dynamic load, the Combo Fructus[®] can be piled up to 8000 kg for long term storage.
- 3. Easy handling: thanks to the floating hinges and unique locking latches on ends, the Combo Fructus® can be erected and folded by a single operator saving labor and time.
- 4. Automation friendly: the 3 sturdy skids are compatible with most automated handling systems and conveyors.

Combo Fructus®



5600.100 - 1060 L - CF 280 1219 x 1118 x 1064 Ext. (mm) 1142 x 1035 x 882 Int. (mm) Weight (Kg) 100.0 Folded height (mm) 322.5 Stacked height (mm) 1034 Folding ratio 69.70 %

5600.200 - 1136 L - CF 300

Folded height (mm) 322.5

Stacked height (mm) 1095

Ext. (mm)

Int. (mm)

Weight (Kg)

Folding ratio



Common Mechanical performances :

Unit load: 1500 kg Stack load: 8000 kg (4/1) Dynamic load: 3200 kg (1/1) Common features :

Solid walls

205

1219 x 1118 x 1125 1142 x 1035 x 943

104.0

71.33 %


- Reinforced solid smooth base
- 3 runners
- Lid included

Combo Excelsior®



1219 x 1016 x 1133 Ext. (mm) Int. (mm) 1142 x 935 x 943 1005 x 1208 Runners Weight (Kg) 90.0 Folded height (mm) 341 Stacked height (mm) 1113 Folding ratio 70.00 % B/D/I/L/U Version Lid included. With bottom discharge

5602.200 - 1000 L - CE 265



Combo Life® top benefits

- 1. NEW. Bisphenol A free material butterfly valve available with 250 and 1000 L liners. Latest EC and French food contact regulations. Reusable IBC with disposable liner and valve prevents contamination.
- 2. Maximized savings: 60% folding ratio allows 5 stacked columns of folded IBC per truck, drastically reducing reverse logistics costs.
- 3. Fast and easy handling: thanks to its design, Combo can be set up and handled by one operator only.
- 4. Tough and long lasting: the double wall structure enables up to 7500 kg stacking load or 4 on 1 piles minimizing storage space. Combo withstands road rail and sea freight with 1400 kg unit load.

800 x 600



430.010 - 264 L	– Combo CL 65
xt. (mm)	805 x 609 x 833
nt. (mm)	740 x 540 x 660
Veight (Kg)	20.0
olded height (mm)	
itacked height (mm)	813
olding ratio	48.00 %
/ersion	B / D / I / U

Lid included.

205

1219 x 1118 x 1186

1142 x 1035 x 1004

107.0

72.80 %

5600.300 - 1192 L - CF 315

Stacked height (mm) 1156

Ext. (mm)

Weight (Kg)

Folding ratio

1155 x 1155



4420.032 - 1060 L - Combo 285 1155 x 1155 x 1132 1065 x 1045 x 940 Weight (Kg) 88.5 Folded height (mm) 450

Stacked height (mm) 1115 Folding ratio 60.00 % B / D / I / L / V



1065 x 1045 x 940 88.5 60.00 % B/D/I/V

Lid included. With bottom discharge plug and tamper evident cap.

Lid included for all models

205

205

Liners and accessories

material valve available



Intermediate Bulk Containers





4430.020 - 264 L Ext. (mm)

Int. (mm) Weight (Kg) Folded height (mm) 383 Stacked height (mm) 813 Folding ratio Version

805 x 609 x 833 740 x 540 x 660 20.0 48.00 % B/D/I/U

With bottom discharge.



4420.038 - 1060 L - Combo 285

Ext. (mm) Int. (mm) Weight (Kg) Folded height (mm) 450 Stacked height (mm) 1115 Folding ratio Version



25

1155 x 1155 x 1132 1065 x 1045 x 940 88.5 60.00 % B/D/I/L/U

Lid included. With bottom discharge



Filling bridge







Tamper evident cap CL 285

TankGo[®] top benefits

1. UN ADR RID IMDG certified manufactured to the utmost rigorous regulations.

- 2. Versatile range: fitting according to content and end uses. Wide variety of ball valves to meet all chemical industry requirements.
- 3. Tough and safe: non slip runners compatible with all handling devices; all surfaces smooth and rounded for operator friendliness, 100% plastic for no maintenance and easy cleansing.





500 L

MRE - 93940C1 - 500 L Ext. (mm) 1160 x 1160 x 895 Weight (Kg) 64/74 Maximum density (Kg/L) 1.9

Stacked during transport 1/1 Stacked unladen 3/1 Max. laden weight (Kg) 1024 Version UN, ADR, RID, IMDG certified

800 L



MSE - 93900C1 - 800 L Ext. (mm) 1160 x 1160 x 1155 Weight (Kg) 83/93 Maximum density (Kg/L) 1.9 Stacked unladen 2/1 Max. laden weight (Kg) 1601 Version UN, ADR, RID, IMDG certified

1000 L



1TE - 90990AM	- 1000 L	A LOZ HDPE
xt. (mm)	1160 x 1160 x 1355	
Veight (Kg)	93/103	
laximum density (Kg/L))1.9	
tacked unladen	2/1	
1ax. laden weight (Kg)	2163	
ersion	UN, ADR, RID, IMDG certified	

Common features

Viton sealing gasket

Ball valve DN50 in GRP,


EPDM sealing gasket

Loading cover: Emptying valves: Vents: Optional: Structural foam pallet base

Threaded DN150 EPDM or Viton sealing gasket Ball valves in PPFV, PE-PVDF and other materials, DN50 2 positions in accordance with legislation

Automatic anti-depression venting Customisation logos, texts Bottle colour: Black / White Pallet colour: Black / Red / Green / Blue / Yellow / Grey

> For TankGo® For TankGo® 3000 500 to 1000L



Common accessories to the TankGo[®] range

EPDM sealing gasket

Cover DN150 special Viton sealing gasket



Threaded cover DN150 EPDM sealing gasket

Two-position venting, Viton sealing gasket



Two-position venting,

Anti-depression venting

Optional:

Optional:



Cover DN400 with or without vent*




Frontal venting, valve DN25

New TankGo[®] 3000 the only 3000L plastic IBC 1. 100% safe and certified: unique 3000L 100% plastic IBC on the market officially approved and certified for the transport and storage of hazardous liquids. 2.100% Anti corrosion: tank pallet and top are made of HDPE, so TankGo® 3000 is oxidation free and maintenance free. 3.100% profitable: Rotationally molded thick walled tank and external structure withstand harsh industrial environments and intensive handling ensuring a long service life.



> Reference	8435000
Use	Transport and storage of hazardous liquids
Version	UN, ADR, RID, IMDG certified
Homologation plate	Fixed in the front part of the IBC
Standard liquids	Water, Acetic Acid, 65% Nitric Acid, Butyl Acetate, Surfactants
Usable volume	2940 litres
Overflow capacity	3000 litres
Maximum density	1.7 gr/cm3
Service life	The bottle must be changed every 5 years
Length x width	2385 x 1570 mm.
Height	1870 mm.
Weight	340 kg.
Stacked unladen	1/1
Maximum gross weight	5.345 kg.
Top screw cap	Threaded DN150 EPDM or Viton sealing gasket
Outlet	Ball valves in PPFV, PE-PVDF, DN50
Ventings	2 positions in accordance with legislation
	Automatic anti-depression venting
	Frontal venting valve
Optional	Customisation logos by mass engraving
Tank colour	Natural
Colour cover/pallet part	Black / Red / Green / Blue



- Safe and easy handling: 4 rigid pivots stand on top of the structure to ensure stable stacking, unladen. Eyebolts are on top for operators safety. Forklift entries are on each side and on the back end.
- Identification and brand awareness: Homologation plate on front end, and multiple customization options: engraving, self-adhesive label areas, and a choice of possible colors for the structure on application.

Ergonomic

Two ladders available, short and long side. Steps with anti-slip surface.

Easy handling

Forklift entries in each long side. One on the back short side.



Anti-depression venting

Preventing collapsing of the tank in case of sudden discharge.

Rotationally molded products

Thanks to our rotational molding manufacturing site located in Spain, we offer an extensive range of tanks, IBC's, large bulk containers and more. Versatility, quality and profitability are the main benefits of the standard and bespoke solutions we offer for storage, anti-spill and many other specific applications.



Product ranges



IBC's and hoppers

Our hoppers and IBCs' are designed and manufactured for intensive, harsh industrial use for many years. From harmless liquids and powders, to the most hazardous products our range ensures, secure, safe, efficient, sustainable and long term logistics solutions.



Spill control equipment

Maximum safety and efficiency complying with the latest EU legislation: Our movable spill control product range, protects operators and environment from spills and leaks. Maintenance free, our solutions are compatible with most used hazardous chemicals.



Rotationally molded storage containers and tanks

Available in many shapes and sizes, our containers are one piece moldings, watertight and suitable for a wide range of liquids. Our dosing tanks are compatible with drinking water. Our thick tanks compliant with APQ-6 norms and are certified for corrosive liquids.

Leading in innovation

Schoeller Allibert creates innovative plastic packaging systems for a better world.

Continuous innovation

Continuous innovation is at the heart of our business. We see it as our task to ensure our clients are prepared for future challenges. In today's competitive markets, advantages resulting from smart design will rapidly translate into improved performance and considerable benefits.

Smart design makes the difference

Foldable containers that are stronger but weigh less will result in less fuel consumption during transport. Containers with 10% more transport volume and 30% less return volume when folded can make the difference in highly competitive markets like the automotive industry or agriculture.

Major innovations in returnable packaging

Many of the major innovations in plastic packaging systems were developed by Schoeller Allibert. We invented products like foldable large containers, such as the Magnum Optimum[®], and bottle crates with in-mould labels. In addition, we invented and optimized production techniques like injection moulding and mirror welding, each time resulting in lighter, stronger and cleaner crates and containers. We take care of all the necessary steps, creating a sustainable packaging cycle.

Do you want to know more ?

Please visit our website www.schoellerallibert.com





Bespoke solutions – customer products

Thanks to our 40 years experience in designing and manufacturing rotationally molded plastic products, we can develop new innovative customer solutions. Our R&D department will create your own solution from design to production of the final piece.

www.schoellerallibert.com







Head Office Netherlands Schoeller Allibert Services B.V. Taurusavenue 35 NL-2132 LS Hoofddorp 00 31 88 0047300

Austria Schoeller Allibert GmbH Rudolf Diesel-Strasse 26 AT-2700 Wr. Neustadt 00 43 2622 206 56

Belgium Schoeller Allibert bvba Industrieweg 143, BE – 3583 Beringen 00 32 11 39 38 38

Czech Republic Schoeller Allibert Czech Republic s.r.o. NA Rovince 879 CZ-720 00 Ostrava 00 420 596 790 010

Finland Schoeller Allibert Oy Askonkatu 9 F FI-15100 Lahti 00 358 848 211

France Schoeller Allibert France 176 avenue Charles de Gaulle FR-92200 Neuilly-sur-Seine 00 33 1 41 20 09 90

7 Germany

(6)

Schoeller Allibert GmbH Vossstrasse 20 DE-10117 Berlin 00 49 30 36471 100

(8) Hunga

(9)

Schoeller Allibert Hungary Kft Szabadság út 117. 2. emelet HU-2040 Budaörs 00 36 23 332 010

Italy Schoeller Allibert S.p.A. Via Enzo Ferrari, 1 - Frazione Zucche IT-10040 Volvera (TO) 00 39 011 39 75 759

Latvia Schoeller Allibert SIA Ritausmas street 2 LV-1058 Riga 00 371 673 822 80

Netherlands Schoeller Allibert B.V. Bruchterweg 88, NL-7772 BJ Hardenberg Postbus 176, NL-7701 AD Hardenberg 00 31 523 727 026

Poland Schoeller Allibert Sp. z o.o. ul. Fryderyka Wilhelma Redena 5 PL-41-808 Zabrze 00 48 32 283 13 10

 Romania

 Schoeller Allibert SRL

 Str Turnu Magurele nr. 270 D

 RO-041713 Bucharest

 00 40 21 460 20 88



Russia
 Schoeller Allibert ZAO
 Business center LETO, office 508
 Sverdlovskaya nab., 44
 RU-195027 St. Petersburg
 00 7 812 326 65 20

Slovakia Schoeller Allibert s.r.o. Kominárska 2,4 SK-831 04 Bratislava 00 421 2 555 65940

(16) Spain Schoeller Allibert, SAU Av. Camí Reial, 8 P.I. Riera de Caldes ES-08184 Palau-Solità i Plegamans, Barcelona 00 34 93 864 0080

7) Sweden Schoeller Allibert Sweden AB Hässelholmsvägen 10, P.O. Box 82 SE-28422 Perstorp 00 46 435 777 000

Switzerland Schoeller Allibert Swiss Sàrl Route de la Condemine 11 CH- 1680 Romont 00 41 266 519 210

United Kingdom & Ireland Schoeller Allibert Limited Road One Industrial Estate GB-CW7 3RA Winsford 00 44 1606 561900

Schoeller Allibert International GmbH Zugspitzstrasse 15 DE-82049 Pullach 00 49 89 638 66 0

Other continents

Logipak Schoeller Allibert SPA Hermanos carrera into 79 Colina, Santiago, Chile 0056 (2) 24815970

hina

Schoeller Allibert China Room 115, Unit A3, No.700 Wanrong Road,Zhabei District CN-200072 Shanghai 00 86 21 31 33 50 80

1exico

Schoeller Allibert International México, S.A. de C.V. Avenida Cafetales 1702 D-205 Col. Hacienda de Coyoacán Delegación Coyoacán C.P. 04970 México D.F. 0049 89 638 66 0

UAE

Schoeller Allibert International Middle East LLC Office 117 Abu Dhabi Airport Business Park PO Box 2131 AE- Abu Dhabi, UAE 00971 2 419 2771

USA

Schoeller Allibert 4320 S. Cotton Lane Suite 200 Goodyear, AZ 85338 00 1 623 889 7970

Schoeller Allibert www.schoellerallibert.com | webshop.schoellerallibert.com