

Cisco D9865 Satellite Receiver

The Cisco[®] D9865 Satellite Receiver is designed for satellite content distribution, and targets the broadcast, business TV, private networks, and SMATV environment. The receiver offers the ability to receive digitally encrypted video, audio, VBI, and data. It provides a cost-effective, variable-rate solution to transition existing DVB[®]-S/MPEG-2 services to DVB-S2/MPEG-4. It also supports MPE IP data.

Figure 1. Cisco D9865 Satellite Receiver



Ease of Use

The unit is set up via the on-screen display menu, using a handheld infrared remote control, or using navigation keys on the front panel of the receiver. User-editable presets are provided for quick re-tuning to other broadcasts. The receiver also supports a Web interface and SNMP control via the Ethernet port as an option.

Free-to-air Reception

This receiver is capable of receiving a DVB/MPEG compliant free-to-air broadcast.

Secured Broadcast Reception

Supporting the PowerVu conditional access with DES or DVB descrambling, or with DVB Conditional Access Module (CAM) based DVB CA systems, this receiver can be used to receive secured corporate communication of video, audio, and data broadcast. It can also be used for secured delivery of TV programming to hotels, MDUs, homes, and commercial establishments such as restaurants and stores.

Data Outputs

Data outputs can be used for distribution of electronic documents, such as price lists and video files. DVB MPE IP data via an Ethernet interface allows for connection to a local area network for larger file transfer or communication with multiple network clients.

Features

- DVB-S QPSK, DVB-S2 QPSK/8PSK demodulation
- Symbol rate from 1.0 to 45 MS/s for DVB-S and from 1.0 to 31 MS/s for DVB-S2
- PowerVu[®] conditional access with DES and DVB descrambling
- CAM interface hardware for DVB CAM-based descrambling
- 4:2:0 High Definition (HD) MPEG-2 and MPEG-4 AVC decoding
- 4:2:0 Standard Definition (SD) MPEG-2 and MPEG-4 AVC decoding
- 4:2:0 NTSC and PAL (B/G/I/D/M/N) video decoding
- MPEG, Dolby[®] Digital, and HE-AAC audio decoding
- DVB Subtitling and DVB VBI (WST, WSS, VPS)
- One unbalanced stereo pair of audio outputs
- Line 21 closed caption and V-chip support
- Fingerprint trigger
- Service replacement
- Field upgradeable software
- Front panel 4-digit LED for channel display
- On-screen display menu for setup and status
- User-editable preset configurations
- MPE data support and Web GUI (D9865D only)
- CAM Interface software
- Dolby Digital Plus

Optional Features

- HDMI and component video outputs for HDTV (D9865H and D9865D only)
- Ethernet 10/100BaseT for IP data, Web interface, SNMP control (D9865D only)

Specifications

Table 1. Product Specifications

Parameter	Value
System	MPEG-2/DVB Compatible EN300 421, EN 300468, H.264
Demodulation	DVB-S QPSK, DVB-S2 QPSK and 8PSK
Tuner	
Number of RF Inputs	1
Input Level	-25 dBm to -65 dBm per carrier
Frequency Range	950 MHz to 2150 MHz
Symbol Rate Range	DVB-S: 1.0 to 45 MSymbols/s DVB-S2: 1.0 to 31 MSymbols/s
Satellites	C-band and Ku-band
Receiver Spectrum Sense	Normal and Inverted
Input Impedance	75 Ω
Analog Video Output	
Number of Channels	1
Connector Type	RCA
Video Decompression Type	MPEG-2 4:2:0, MPEG-4 4:2:0
Level	1.0 V pp \pm 10%
Video Standard	NTSC and PAL B/G/I/D/M/N, supports HD down-conversion
Digital Audio/Video Output (D9865H and D9865D only)	
Number of Outputs	1 HDMI digital audio/video output, supports SD-to-HD up-conversion
HD Analog Video Output (D9865H and D9865D only)	
Number of Outputs	1 component (Y, Pb, Pr) HD analog video output
Analog Audio Output	
Number of Channels	1 stereo pair or 2 mono channels
Connector Type	RCA
Output Level	Unbalanced, 2 V rms \pm 10% at 0 dBFS
Audio Decompression	MPEG 1 Layer 2, Dolby Digital Plus, HE-AAC
Digital Audio S/PDIF Output	
Connector Type	RCA
VBI	
NTSC	Lines 10 to 22 fields 1 and 2
PAL	Lines 7 to 22 fields 1 and 2 WST, WSS, VPS
Data Outputs	
Ethernet Output for IP data	
Connector	RJ-45, 10/100BaseT
Environmental Specifications	
Operating Temperature	0 - 50°C (32 - 122°F)
Storage	-20 - 70°C (-4 - 158°F)
Chassis Mechanical Specifications	
Height	2.36 in. (6.0 cm)

Parameter	Value
Width	11.69 in. (29.7 cm)
Depth	7.68 in. (19.5 cm)
Weight	5 lbs (2.3 kg)
Power	
Voltage Range	100 V to 240 VAC
Line Frequency	50/60 Hz
Power Consumption	35 W max.
LNB Power on satellite input	+13 V/+18 V @ 350 mA max.

Figure 2. Cisco D9865B Satellite Receiver Rear Panel (Base unit – SD Video Decoding)




Figure 3. Cisco D9865H Satellite Receiver Rear Panel (Base SD and HD output version with HDMI)





Figure 4. Cisco D9865D Satellite Receiver Rear Panel (Full-featured with HDMI and Data)



Ordering Information

Table 2. Ordering Information

Cisco D9865 Satellite Receiver	Part Number
D9865B (Base version with SD only outputs/HD Down-conversion)	
NTSC CH3/4 Modulator with NA cord	4028651000001
PAL UHF CH21-69 modulator with Euro plug	4028651020005
PAL UHF CH21-69 modulator with no power cord (select from below)	4028651020000
D9865H (Base SD and HD output version)	
NTSC CH3/4 Modulator with NA cord	4028651040001

Cisco D9865 Satellite Receiver	Part Number
PAL UHF CH21-69 modulator with Euro plug	4028651060005
PAL UHF CH21-69 modulator with no power cord	4028651060000
D9865D (SD and HD output version with data interfaces)	
NTSC CH3/4 Modulator with NA cord	4028651120001
PAL UHF CH21-69 modulator with Euro plug	4028651140005
PAL UHF CH21-69 modulator with no power cord (select from below)	4028651140000
Power Cords	
UK power cord	1002798
Euro power cord	503414
Australia power cord	1002604
Argentina power cord	1002655
Brazil power cord	1003648
China power cord	1003670
India power cord	1003667

With respect to each AVC/H.264 product, we are obligated to provide the following notice:

AVC VIDEO LICENSE

THIS PRODUCT IS LICENSED UNDER THE AVC PATENT PORTFOLIO LICENSE FOR THE PERSONAL AND NON-COMMERCIAL USE OF A CONSUMER TO (i) ENCODE VIDEO IN COMPLIANCE WITH THE AVC STANDARD ("AVC VIDEO") AND/OR (ii) DECODE AVC VIDEO THAT WAS ENCODED BY A CONSUMER ENGAGED IN A PERSONAL AND NON-COMMERCIAL ACTIVITY AND/OR WAS OBTAINED FROM A VIDEO PROVIDER LICENSED TO PROVIDE AVC VIDEO. NO LICENSE IS GRANTED OR SHALL BE IMPLIED FOR ANY OTHER USE. ADDITIONAL INFORMATION MAY BE OBTAINED FROM MPEG LA, L.L.C. SEE <http://www.mpegla.com>.

Accordingly, please be advised that service providers, content providers, and broadcasters are required to obtain a separate use license from MPEG LA prior to any use of AVC/H.264 encoders and/or decoders.

Service and Support

Using the Cisco Lifecycle Services approach, Cisco and its partners provide a broad portfolio of end-to-end services and support that can help increase your network's business value and return on investment. This approach defines the minimum set of activities needed by technology and by network complexity to help you successfully deploy and operate Cisco technologies and optimize their performance throughout the lifecycle of your network.

How to buy

To view buying options and speak with a Cisco sales representative, visit www.cisco.com/c/en/us/buy.

For More Information

To learn more about this product, contact your local account representative.

To subscribe to receive end-of-life/end-of-sale information, go to <http://www.cisco.com/cisco/support/notifications.html>.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Dolby and the double-D symbol are trademarks of Dolby Laboratories.

The DVB logo is a registered trademark of the DVB Digital Video Broadcasting Project.