

ProGrid® Compo GC Ultra-T

Polyester Geogrid Composite

Provides a good bond with asphalt in managing reflective / stress cracks



Product Information

ProGrid® Compo GC Ultra-T is a bitumen coated high modulus Polyester (PET) geogrid which is fully stitch bonded with an integral Polypropylene (PP) ultra-lightweight porous nonwoven geotextile backing. The geogrid composite has a bituminous coating to provide a good bond with asphalt layers with increased chemical resistance.

ProGrid® Compo GC Ultra-T series can not only increase the tensile strength of the asphalt layer(s) and extend the service life of pavement layer(s), but also decreases the occurrence rate, magnitude and severity of reflective cracking under cyclic traffic loads including the retardation of stress cracks associated with joint interfaces. With a high modulus, high temperature resistance and high bonding properties, ProGrid® Compo GC Ultra-T can be used below asphalt overlays or as an asphalt interlayer in new roads or rehabilitation works for reinforcement.

Applications

- Local road and highway pavements
- Composite pavements
- Airport pavements
- Road resurfacing, widening and repair
- Joint interfaces

ProGrid® Compo GC Ultra-T

Product Data Sheet

Product Grade


Typical Properties	Test Method	Units	GC 50/50***	GC 100/100***
Ultimate Tensile Strength (MD/CMD)	ASTM D6637	kN / m	≥ 50 / 50	≥ 100 / 100
Elongation at Break (MD/CMD)	ASTM D6637	%	≤ 12 / 12	≤ 12 / 12
Tensile Strength at 2% elongation (MD/CMD)	ASTM D6637	kN / m	≥ 10 / 10	≥ 17 / 17
Aperture Size		mm	33	33
Installation Damage Resistance	EN ISO 10722	%	≥ 90	≥ 90
Melting Point - Geogrid	ASTM D276	°C	≥ 250	≥ 250
Melting Point - Geotextile		°C	≥ 150	≥ 150
Geotextile Mass*	AS 3706.1	g / m ²	20*	20*
Standard Roll Width**		m	3.95**	3.95**
Standard Roll Length**		m	100**	100**

MD = Machine Direction, CMD = Cross Machine Direction

* Polypropylene (PP) ultra-light weight geotextile mass is ≥ 20g/m² to provide an option for the lower end requirements under Qld TMR MRTS104. A range of geotextile mass is available on request to suit specific projects requirements.

** Other roll dimensions are available to suit project requirements.

*** May require an extended lead time, please contact Global Synthetics for more information.



About Us

Leaders in Geosynthetics

Global Synthetics is a 100% Australian-owned company, proud to offer a complete range of high-quality geosynthetic products backed by over 200 years of combined staff experience in the industry.

We have supplied products to some of the largest recent infrastructure works in Australia. Global Synthetics provides major benefits to any geotechnical engineering project with the right products and our technical expertise.

Global Synthetics products are used in the following applications:

- Pavement Stabilisation
- Ground Improvement
- Soil Reinforcement and Retaining Structures
- Water Management
- Drainage Systems & Hydraulic Works
- Landfills
- Coastal Erosion Structures

Get in Touch

AUSTRALIA

Website

globalsynthetics.com.au

Email

info@globalsynthetics.com.au

New South Wales

(02) 9725 4321

North Queensland

(04) 5921 1692

Victoria/Tasmania

(03) 9791 1772

Queensland

(07) 3865 7000

South Australia

(08) 8384 8894

Western Australia

(08) 9459 4300

NEW ZEALAND

Email


info@globalsynthetics.co.nz

Auckland

0800 510 120

Christchurch

0800 510 120



All information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Global Synthetics Pty Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Global Synthetics Pty Ltd have a policy of continuous development so information and product specifications may change without notice.



Global Synthetics
LEADERS IN GEOSYNTHETICS