



flow, stop and go®



PR-TYPE CHECK VALVES

Features: with integrated pressure relief

- Nominal size: 14 – 20 mm
- Installation: in or against direction of flow - depending on type
- Design: cartridge style (DW)
open version (NV, OV, OF)

designation	flow range (l/min)	flow range (gpm)	part number	bore diameter
DW14/DN10-AF-PR	3.0 - 16.8	0.8 - 4.4	304037000	14.1 mm
DW14/DN10-PR	3.0 - 16.8	0.8 - 4.4	304032000	14.4 mm
DW15/DN10-PR	3.6 - 21.0	1.0 - 5.5	304094000	15.1 mm
NV15/DN15-PR	12.6 - 45.0	3.3 - 11.9	310068000	15.1 mm
OV15/DN15-PR	12.6 - 45.0	3.3 - 11.9	310070000	15.1 mm
OF15/DN15-PR	12.6 - 45.0	3.3 - 11.9	310069000	15.1 mm
NV20/DN20-PR	24.0 - 81.0	6.3 - 21.4	310071000	20.1 mm
OV20/DN20-PR	24.0 - 81.0	6.3 - 21.4	310072000	20.1 mm
OF20/DN20-PR	24.0 - 81.0	6.3 - 21.4	314289000	20.1 mm