



flow, stop and go®



HT-TYPE CHECK VALVES

Features: for high tech and hot water applications

Nominal size: 10 – 50 mm
Installation: in or against direction of flow - depending on type
Design: open version

designation	flow range (l/min)	flow range (gpm)	part number	bore diameter
OF10/DN6-HT	2.0 - 16.2	0.5 - 4.3	314394000	10.1 mm
OD13/DN10-HT	1.5 - 25.2	0.4 - 6.7	314335000	13.1 mm
OV15/DN15-HT	12.6 - 45.0	3.3 - 11.9	310022000	15.1 mm
OF15/DN15-HT	12.6 - 45.0	3.3 - 11.9	310024000	15.1 mm
NV20/DN20-HT	24.0 - 81.0	6.3 - 21.4	310011000	20.1 mm
OV20/DN20-HT	24.0 - 81.0	6.3 - 21.4	310012000	20.1 mm
OV25/DN25-HT	25.8 - 127.2	6.8 - 33.6	310028000	25.1 mm
OV32/DN32-HT	51.0 - 234.0	13.5 - 61.8	310030000	32.1 mm
OV40/DN40-HT	75.0 - 360.0	19.8 - 95.1	310046000	40.1 mm
OV50/DN50-HT	204.0 - 540.0	53.9 - 142.7	314350000	50.1 mm