



flow, stop and go®

L-TYPE FLOW REGULATORS



L

Bore diameter: 22.9 mm

Max. temperature: 65°C / 150°F

Pressure range: 1-10 bar / 15-145 psi

color flow regulator	designation	flow rate	part number	divergent pressure range
	L	20.0 l/min	<u>586640100</u>	1-10 bar / 15-145 psi
	L	25.0 l/min	<u>586645100</u>	1-10 bar / 15-145 psi
	L	30.0 l/min	<u>586646100</u>	2-8 bar / 29-116 psi
	L	35.0 l/min	<u>586647100</u>	2-10 bar / 29-145 psi
	L	38.0 l/min	<u>586648100</u>	2-10 bar / 29-145 psi
	L	50.0 l/min	<u>586650100</u>	2-10 bar / 29-145 psi
	L	70.0 l/min	<u>586655100</u>	2-10 bar / 29-145 psi
	L	90.0 l/min	<u>586658100</u>	2-10 bar / 29-145 psi
	L	100.0 l/min	<u>586660100</u>	2-10 bar / 29-145 psi



flow, stop and go®



L-US

Bore diameter: 22.9 mm

Max. temperature: 150°F / 65°C

Pressure range: 20-100 psi / 1.4-6.9 bar

color flow regulator	designation	flow rate	part number	divergent pressure range
	L-US	10.0 gpm max.	<u>587458100</u>	
	L-US	12.0 gpm max.	<u>587459100</u>	
	L-US	13.0 gpm max.	<u>587460100</u>	
	L-US	15.0 gpm max.	<u>587462100</u>	
	L-US	20.0 gpm max.	<u>587463100</u>	
	L-US	25.0 gpm max.	<u>587465100</u>	30-100 psi / 2.1-6.9 bar
	L-US	30.0 gpm max.	<u>587468100</u>	30-100 psi / 2.1-6.9 bar