




flow, stop and go®

PCW01-TYPE FLOW REGULATORS



PCW01

Bore diameter: G 1/2"


Temperature: 65°C / 150°F

Pressure range: 1-10 bar / 15-145 psi

PCW-01 1/2" Flow Regulators				
color flow regulator	designation	flow rate	part number	divergent pressure range
	PCW01	2.0 l/min	588632100	
	PCW01	3.0 l/min	588633100	
	PCW01	4.0 l/min	588634100	
	PCW01	5.0 l/min	588635100	
	PCW01	6.0 l/min	588636100	
	PCW01	7.0 l/min	588637100	
	PCW01	8.0 l/min	588638100	
	PCW01	9.0 l/min	588639100	
	PCW01	10.0 l/min	588640100	
	PCW01	11.0 l/min	588641100	
	PCW01	12.0 l/min	588642100	1.5-10 bar / 21.8-145 psi
	PCW01	15.0 l/min	588650100	2-10 bar / 29-145 psi



flow, stop and go®



PCW01-US

Bore diameter: G 1/2 "


Max. temperature: 150°F / 65°C

Pressure range: 15-100 psi / 1-6.9 bar

color flow regulator	designation	flow rate	part number
	PCW01-US	0.35 gpm max.	588630100
	PCW01-US	0.5 gpm max.	588643100
	PCW01-US	1.0 gpm max.	588644100
	PCW01-US	1.5 gpm max.	588645100
	PCW01-US	1.75 gpm max.	588646100
	PCW01-US	2.0 gpm max.	588647100
	PCW01-US	2.2 gpm max.	588648100
	PCW01-US	2.5 gpm max.	588649100



flow, stop and go®



PCW01-VS

Feature: With dome screen

Bore diameter: G 1/2 "

Max. temperature: 65°C / 150°F

Pressure range: 0.2-4bar / 2.9-58 psi

color flow regulator	designation	flow rate	part number
	PCW01-VS	9 l/min	<u>589637100</u>
	PCW01-VS	10 l/min	<u>589638100</u>
	PCW01-VS	12 l/min	<u>589639100</u>
	PCW01-VS	15 l/min	<u>589640100</u>