



# WV-TYPE CHECK VALVES

**Features:** for water meters, removable for easy exchange

Size: 15 – 40 mm | corresponding bore diameter: 15.1 - 40.1 mm

Installation: against direction of flow

Design: closed, with axial sealing

designation	bore diameter	recommended flow rate		sealing material	part number
		l/min	gpm		
WV15/DN15-EPDM	15.1 mm	12.6 - 45.0	3.3 - 11.9	EPDM	<a href="#">310127000</a>
WV20/DN20-EPDM	20.1 mm	24.0 - 81.0	6.3 - 21.4	EPDM	<a href="#">310128000</a>
WV25/DN25-EPDM	25.1 mm	27.0 - 129.0	7.1 - 34.1	EPDM	<a href="#">310136000</a>
WV40/DN40-EPDM	40.1 mm	75.0 - 360.0	19.8 - 95.1	EPDM	<a href="#">310380000</a>
WV15/DN15	15.1 mm	12.6 - 45.0	3.3 - 11.9	NBR	<a href="#">314217000</a>
WV20/DN20	20.1 mm	24.0 - 81.0	6.3 - 21.4	NBR	<a href="#">314222000</a>
WV25/DN25	25.1 mm	27.0 - 129.0	7.1 - 34.1	NBR	<a href="#">314227000</a>
WV40/DN40	40.1 mm	75.0 - 360.0	19.8 - 95.1	NBR	<a href="#">314247000</a>