



flow, stop and go®



WV-TYPE CHECK VALVES

Features: for water meters, removable for easy exchange

- Size:15 – 40 mm | corresponding bore diameter: 15.1 - 40.1 mm
- Installation:against direction of flow
- Design:closed, with axial sealing

designation	bore diameter	recommended flow rate				sealing material	part number
		l/min		gpm			
WV15/DN15-EPDM	15.1 mm	12.6 -	45.0	3.3 -	11.9	EPDM	310127000
WV20/DN20-EPDM	20.1 mm	24.0 -	81.0	6.3 -	21.4	EPDM	310128000
WV25/DN25-EPDM	25.1 mm	27.0 -	129.0	7.1 -	34.1	EPDM	310136000
WV40/DN40-EPDM	40.1 mm	75.0 -	360.0	19.8 -	95.1	EPDM	310138000
WV15/DN15	15.1 mm	12.6 -	45.0	3.3 -	11.9	NBR	314217000
WV20/DN20	20.1 mm	24.0 -	81.0	6.3 -	21.4	NBR	314222000
WV25/DN25	25.1 mm	27.0 -	129.0	7.1 -	34.1	NBR	314227000
WV40/DN40	40.1 mm	75.0 -	360.0	19.8 -	95.1	NBR	314247000